Features

- Advanced Trench Process Technology
- High Density Cell Design for Ultra Low On-Resistance
- Reliable and Rugged
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

P-CHANNEL MOSFET


Maximum Ratings

- Operating Junction Temperature Range : -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 1.79°C/W Junction to Case (Note 1)


Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DS}	-100	V
Gate-Source Volltage		V_{GS}	±20	V
Continuous Drain Current	T_C=25°C	I_D	-20	A
	T_C=100°C		-12	A
Pulsed Drain Current		I_{DM}	-72	A
Single Pulsed Avalanche Energy(Note 2)		E_{AS}	225	mJ
Total Power Dissipation		P_D	70	W

Note: 1.Surface Mounted on FR4 Board, t ≤ 10 sec.
2. L=0.5mH, V_{DD}=-50V, V_G=-10V,R_G=25Ω,Starting T_J=25°C.

Internal Structure



DPAK(TO-252)



1. Gate
2,4. Drain
3. Source

DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.087	0.094	2.20	2.40	
B	0.000	0.005	0.00	0.13	
C	0.026	0.034	0.66	0.86	
D	0.018	0.023	0.46	0.58	
E	0.256	0.264	6.50	6.70	
F	0.201	0.215	5.10	5.46	
G	0.190		4.83		TYP.
H	0.236	0.244	6.00	6.20	
I	0.086	0.094	2.18	2.39	
J	0.386	0.409	9.80	10.40	
K	0.114		2.90		TYP.
L	0.055	0.067	1.40	1.70	
M	0.063		1.60		TYP.
O	0.043	0.051	1.10	1.30	
Q	0.000	0.012	0.00	0.30	
V	0.211		5.35		TYP.

Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS}=0V, I_D=-250μA	-100			V
Gate-Source Leakage Current	I_{GSS}	V_{DS}=0V, V_{GS} =±20V			±20	μA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-100V, V_{GS}=0V			-1	μA
Gate-Threshold Voltage(Note 3)	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=-250μA	-1	-1.9	-3	V
Drain-Source On-Resistance(Note 3)	$R_{DS(on)}$	V_{GS}=-10V, I_D=-16A	85	100	116	mΩ
Forward Tranconductance(Note 3)	g_{FS}	V_{DS}=-50V, I_D=-10A	5			S
Dynamic Characteristics(Note 4)						
Input Capacitance	C_{iss}	V_{DS}=-25V,V_{GS}=0V,f=1MHz		2100		pF
Output Capacitance	C_{oss}			590		
Reverse Transfer Capacitance	C_{rss}			140		
Total Gate Charge	Q_g	V_{DS}=-80V,V_{GS}=-10V,I_D=-16A		61		nC
Gate-Source Charge	Q_{gs}			14		
Gate-Drain Charge	Q_{gd}			29		
Turn-On Delay Time	$t_{d(on)}$	V_{DD}=-50V,I_D=-16A V_{GS}=-10V,R_{GEN}=9.1Ω		16		ns
Turn-On Rise Time	t_r			73		
Turn-Off Delay Time	$t_{d(off)}$			34		
Turn-Off Fall Time	t_f			57		
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I_S	T_C=25°C			-18	A
Body Diode Voltage	V_{SD}	I_S=-10A, V_{GS}=0V			-1.2	V
Reverse Recovery Time	t_{rr}	I_F=-16A,di/dt=100A/μs		88.3		ns
Reverse Recovery Charge	Q_{rr}			65.9		nC
Forward Turn-on Time	t_{on}	Intrinsic Turn-On Time is Negligible(Turn-On is Dominated by L_S+L_D)				

Note 3. Pulse Test : Pulse Width≤300μs, Duty Cycle ≤2%.

4. Guaranteed by Design, Not Subject to Production Testing.

Curve Characteristics

Fig. 1 - Typical Output Characteristics




Fig. 2 - $R_{DS(ON)}$—Temperature




Fig. 3 - $R_{DS(ON)}$—I_D




Fig. 4 - Total Gate Charge Characteristics





Fig. 5 - Safe Operation Area



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 2.5Kpcs/Reel

Note : Adding "-HF" Suffix for Halogen Free, eg. Part Number-TP-HF

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . ***Micro Commercial Components Corp*** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold ***Micro Commercial Components Corp*** . and all the companies whose products are represented on our website, harmless against all damages. ***Micro Commercial Components Corp***. products are sold subject to the general terms and conditions of commercial sale, as published at
https://www.mccsemi.com/Home/TermsAndConditions.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.