

Features

- Very Low FOM $R_{DS(on)} \times Q_g$
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Halogen Free. "Green" Device (Note 1)
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings

- Operating Junction Temperature Range : -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 62°C/W Junction to Ambient
- Thermal Resistance: 1.6°C/W Junction to Case


Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V _{DS}	650	V
Gate-Source Voltage		V _{GS}	±30	V
Continuous Drain Current		I _D	11	A
Pulsed Drain Current ^(Note 2)		I _{DM}	33	A
Single Pulse Avalanche Energy ^(Note 3)		E _{AS}	211	mJ
Avalanche Current ^(Note 2)		I _{AR}	1.6	A
Repetitive Avalanche Energy ^(Note 2)		E _{AR}	0.32	mJ
Total Power Dissipation	T _C =25°C	P _D	78	W

Note: 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

2. Repetitive Rating, Pulse Width Limited by Maximum Junction Temperature.


3. $I_{AS}=1.6\text{A}$, $V_{DD}=50\text{V}$, $R_G=25\Omega$, Starting $T_J=25^\circ\text{C}$.

Internal Structure



N-CHANNEL Super-Junction Power MOSFET

DFN5060



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.031	0.047	0.80	1.20	
B	0.010		0.254		TYP.
C	0.193	0.222	4.90	5.64	
D	0.232	0.250	5.90	6.35	
E	0.148	0.167	3.75	4.25	
F	0.126	0.154	3.20	3.92	
G	0.189	0.213	4.80	5.40	
H	0.222	0.239	5.65	6.06	
K	0.045	0.059	1.15	1.50	
J	0.012	0.020	0.30	0.50	
L	0.046	0.054	1.17	1.37	
M	0.012	0.028	0.30	0.71	
N	0.016	0.028	0.40	0.71	

Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} =0V, I _D =250μA	650			V
Gate-Source Leakage Current	I _{GSS}	V _{DS} =0V, V _{GS} =±30V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} =650V, V _{GS} =0V			1	μA
		V _{DS} =650V, V _{GS} =0V, T _J =150°C			100	
Gate-Threshold Voltage	V _{GS(th)}	V _{DS} =V _{GS} , I _D =250μA	2.5		4	V
Drain-Source On-Resistance ^(Note 4)	R _{DS(on)}	V _{GS} =10V, I _D =5.5A		0.34	0.38	Ω
Forward tranconductance ^(Note 4)	g _{FS}	V _{DS} =10V, I _D =5.5A		7.8		S
Dynamic Characteristics ^(Note 5)						
Input Capacitance	C _{iss}	V _{DS} =50V, V _{GS} =0V, f=1MHz		901		pF
Output Capacitance	C _{oss}			50		
Reverse Transfer Capacitance	C _{rss}			5.5		
Total Gate Charge	Q _g	V _{DD} =520V, V _{GS} =10V, I _D =11A		21		nC
Gate-Source Charge	Q _{gs}			4.5		
Gate-Drain Charge	Q _{gd}			7		
Turn-On Delay Time	t _{d(on)}	V _{DD} =400V, I _D =11A, R _G =25Ω		41		ns
Turn-On Rise Time	t _r			20		
Turn-Off Delay Time	t _{d(off)}			123		
Turn-Off Fall Time	t _f			6.4		
Drain-Source Body Diode Characteristics						
Continuous Body Diode Current	I _S	T _C =25°C			9.2	A
Pulsed Diode Forward Current	I _{SM}				29	
Body Diode Voltage	V _{SD}	I _{SD} =11A, V _{GS} =0V		0.9	1.2	V
Reverse Recovery Time	t _{rr}	V _R =520V, I _F =I _S , di _F /dt=100A/μs		280		ns
Reverse Recovery Charge	Q _{rr}			2.8		μC
Peak Reverse Recovery Current	I _{rrm}			17		A

Note 4. Pulse Test : Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 1\%$.

5. Guaranteed by Design, Not Subject to Production Testing.

Curve Characteristics

Fig. 1 - Typical Output Characteristics




Fig. 2 - Transfer Characteristics




Fig. 3 - $R_{DS(ON)} - I_D$




Fig. 4 - Capacitance Characteristics




Fig. 5 - Total Gate Charge Characteristics





Fig. 6 - Normalized On Resistance Characteristics



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 5Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp** . does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp** . and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.