Ratings
Voltage: 300 V
Temperature: -10 to 105 °C
Flammability: VW-1

Conductor
Conductor count: 2
Gauge: 26 AWG 0.14 mm²
Material: tinned copper strands
Strand size: Ø 0.16 mm x 7

Outer jacket
Material: PVC/38P
Color: white
Diameter: 2.7 ±0.20 mm (1.35 ±0.1 x 2)
Nominal thickness: 0.40 mm

Electrical requirements
Voltage test: 300 V
Spark test: 3.0 kV
Conductor maximum resistance at 20 °C: 150 ohms/km
Jacket resistance at 20 °C: 10 Mohms/km
Dielectric test: 2000 Vac for 1 minute with no breakdown

Mechanical requirements
Jacket tensile strength: 1.05 kgf/mm²
After aging at 136±2 °C for 7 days:
Minimum tensile strength 70% of original
Minimum elongation 65% of original

Environmental requirements
Heat shock: 136±1 °C/1 hour, no observed degradation
Deformation: 136±1 °C/1 hour, ≤50%
Cold bend: -10±2 °C/1 hour, no observed cracking

Wire marking: E339579 UL AWM STYLE 2651 26 AWG 105°C 300V VW-1 - - - cUL AWM I A 105°C 300V FT1 TENSILITY



Revision:	Date:	Description:
A	3/02/2017	Initial release

Prepared: AG Digitally signed by AG Date: 2017.10.20 11:49:49 -07'00'

Verified: GL Digitally signed by GL Date: 2017.10.23 16:44:44 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:
RoHS and REACH compliant

Function test: no open, no short circuit, no intermittent

Description:
Wire, 2C TS, 26 AWG, UL2651, 300V, 105C, 2.7 mm, VW-1, PVC, 38P, white

TENSILITY
tel 1.541.323.3228 800 877.670.7118
fax 1.541.323.4202 web tensility.com

Size: A
Part number: 30-00806
Scale: 20:1
Sheet 1 of 1

5 4 3 2 1