ADELS contact

Screw Terminal Blocks

1000/ 3 DS



terminal block, 3 pole, insulating material: PA 6, cross-section rating: 6.0 mm², pin spacing: 12.00 mm, mounting hole diameter: 3.6 mm, wire protector (DS): yes, fixing: screw, voltage rating: 500 V, current rating: 41.0 A

Order Info

reference number (ref. no.)	125303
PU	400
EAN	4028012100880

Type

type	terminal block
number of poles	3 pole
clamping units per pole	1
colour	natural
cross-section rating	6.0 mm²
connection type	screw
wire protector (DS)	yes

Technical Data

voltage rating	500 V
current rating	41.0 A
insulating material	PA 6
contact material	brass
core cross-section min.	0.5 mm²
core cross-section max.	6.0 mm²
flammability rating	V-2
min. Umgebungstemperatur	-40 °C
max. Ambient Temperature Operation	85 °C
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.5-8.0 mm
mounting hole diameter	3.6 mm
pin spacing	12.00 mm
fixing	screw

Approvals

acc. to EN 60998	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

1000 BZ/ 3	191403
ABK 406/ 3	193303
ZEL 110	196420