

# Han B Hood Side Entry HC 4 Pegs PG 29



•	
Part number	09 30 724 0521
Specification	Han B Hood Side Entry HC 4 Pegs PG 29
HARTING eCatalogue	https://b2b.harting.com/09307240521

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han <sup>®</sup> B
Type of hood/housing	Hood
Description of hood/housing	Black
Туре	High construction

#### Version

Size	24 B
Version	Side entry
Cable entry	1x Pg 29
Locking type	Double locking lever
Field of application	Standard hoods/housings for industrial connectors

# **Technical characteristics**

Limiting temperature	-40 +125 °C
	IP65
Degree of protection acc. to IEC 60529	IP66
	IP67
	4
Type rating acc. to UL 50 / UL 50E	4X
	12

## Material properties

Material (hood/housing) Aluminium die-cast
--

Page 1 / 2 | Creation date 2022-01-15 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## Material properties

Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 9005 (jet black)
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
Specifications and approvals	
Specifications and approvals Approvals	DNV GL
	DNV GL Yes
Approvals	
Approvals CE	
Approvals CE Commercial data	Yes
Approvals CE Commercial data Packaging size	Yes 1
Approvals CE Commercial data Packaging size Net weight	Yes 1 266.8 g