

## Specification Sheet

Part Number: 157-00035



Mount provides low insertion and high extraction forces which makes for a strong and easy installation.

Tie utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.

Clamping rails increase grip on round bundles.

Thinner strap provides increased flexibility for improved ergonomics.

Wide Strap Cable Tie with 8mm Stud Mount, 12.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag

**Article Number** 157-00035

**Type** WSI8MM

**Color** Black (BK)

**Quantity Per** bag

**Product Description** The Wide Strap Stud Mount Cable Tie minimizes pinching on soft bundles and features a low profile head to provide compact bundling. A thinner strap provides increased flexibility for improved ergonomics. Available in various stud mount sizes, the wide strap tie utilizes a strong hinge between the stud mount and head to provide superior holding ability on a threaded stud.

**Short Description** Wide Strap Cable Tie with 8mm Stud Mount, 12.7" Long, .5" Wide, PA66HIRHSUV, Black, 300/Bag

**Global Part Name** WSI8MM-PA66HIRHSUV-BK

**Minimum Tensile Strength (Imperial)** 120.0

**Minimum Tensile Strength (Metric)** 535.0

**Length L (Imperial)** 12.7

**Length L (Metric)** 322.6

**Fixation Method** Weld Stud Fixing

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.5

**Width W (Metric)** 12.7

**Bundle Diameter Min (Imperial)** 0.38

**Bundle Diameter Min (Metric)** 9.5

**Bundle Diameter Max (Imperial)** 3.25

**Bundle Diameter Max (Metric)** 82.5

<b>Stud Diameter (Metric)</b>	M8
<b>Stud Diameter (Imperial)</b>	5/16
<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL 94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Package Quantity (Imperial)</b>	300
<b>Package Quantity (Metric)</b>	300
<b>Customs Number</b>	3926909988