

HCMA1 104

Automotive grade High current power inductors



Product features

- AEC-Q200 qualified
- High current carrying capacity
- Magnetically shielded, low EMI
- Frequency range up to 5 MHz
- Inductance range from 0.2 μ H to 22 μ H
- Current range from 5 A to 45 A
- 11.5 mm x 10.3 mm footprint surface mount package in a 4.0 mm height
- Iron powder core material

Applications

- Body electronics
 - Central body control module
 - Vehicle access control system
 - Headlamps, tail lamps and interior lighting
 - Heating ventilation and air conditioning controllers (HVAC)
 - Doors, window lift and seat control
- Advanced driver assistance systems
 - Adaptive cruise control (ACC)
 - Automatic parking control
 - Collision avoidance system
 - Car black box system
- Infotainment and cluster electronics
 - Audio subsystem: head unit and trunk amp
 - Digital instrument cluster
 - In-vehicle infotainment (IVI) and navigation
- Chassis and safety electronics
 - Airbag control unit
 - Electronic stability control system (ESC)
 - Electric parking brake Voltage Regulator Module (VRM)

Environmental data

- Storage temperature range (Component): -55 °C to +125 °C
- Operating temperature range: -55 °C to +125 °C (ambient + self-temperature rise)
- Solder reflow temperature: J-STD-020 (latest revision) compliant




Product Specifications

Part Number ⁷	OCL ¹ (μH) $\pm 20\%$	FLL ² (μH) minimum	I_{rms}^3 (A)	$I_{\text{sat}}^{4,5}$ (A)	DCR (m Ω) typical @ +20 °C	DCR (m Ω) maximum @ +20 °C	K-factor ⁶
HCMA1104-R20-R	0.20	0.13	32	45	0.63	0.72	411
HCMA1104-R36-R	0.36	0.23	30	42	1.04	1.20	269
HCMA1104-R45-R	0.45	0.29	29	36	1.07	1.23	219
HCMA1104-R56-R	0.56	0.36	25	32	1.56	1.80	230
HCMA1104-R90-R	0.90	0.58	22	28	2.17	2.50	236
HCMA1104-1R0-R	1.0	0.56	18	28	3.0	3.3	378
HCMA1104-1R5-R	1.5	0.84	16	32	3.8	4.2	310
HCMA1104-2R2-R	2.2	1.23	12	18	6.0	7.0	253
HCMA1104-3R3-R	3.3	1.85	10	16	10.8	11.8	220
HCMA1104-4R7-R	4.7	2.63	8.5	15	17	20	175
HCMA1104-100-R	10	5.60	7.5	8.5	27	30	116
HCMA1104-220-R	22	12.3	5.0	5.5	60	66	92


- Open Circuit Inductance (OCL) Test Parameters: 100 kHz, 0.25 Vrms, 0.0 Adc, @ +25 °C
- Full Load Inductance (FLL) Test Parameters: 100 kHz, 0.25 Vrms, @ I_{sat} , @ +25 °C
- I_{sat} : DC current for an approximate temperature rise of 40 °C without core loss. Derating is necessary for AC currents. PCB layout, trace thickness and width, air-flow, and proximity of other heat generating components will affect the temperature rise. It is recommended that the temperature of the part not exceed +125 °C under worst case operating conditions verified in the end application.
- I_{sat} : Peak current for approximately 20% rolloff @ +25 °C- HCM1104-R20-R to HCM1104-R90-R

- I_{sat} : Peak current for approximately 30% rolloff @ +25 °C HCM1104-1R0-R to HCM1104-220-R
- K-factor: Used to determine B_{50} for core loss (see graph). $B_{p-p} = K * L * \Delta I$. B_{p-p} : (Gauss), K: (K-factor from table), L: (Inductance in μH), ΔI (Peak to peak ripple current in Amps).
- Part Number Definition: HCM1104-xxx-R
HCM1104 = Product code and size
xxx= inductance value in μH , R= decimal point,
If no R is present then last character equals number of zeros
-R suffix = RoHS compliant


Dimensions (mm)



Recommended pad layout




Schematic





Part marking: A=automotive grade, xxx=inductance value in μH , R= decimal point. If no R is present then last character equals number of zeros.
wlyy=date code, R=revision level
All soldering surfaces to be coplanar within 0.1 millimeters
Tolerances are ± 0.3 millimeters unless stated otherwise
Color: Grey
Do not route traces or vias underneath the inductor

Packaging information (mm)

Supplied in tape and reel packaging, 850parts per 13" diameter reel




Temperature rise vs. total loss




Core loss vs. B_{p-p}

HCMA1104-R20-R to HCMA1104-R90-R




HCMA1104-1R0-R to HCMA1104-220-R




Inductance characteristics


HCMA1104-R20-R




HCMA1104-R36-R




HCMA1104-R45-R




HCMA1104-R56-R









HCMA1104-R90-R



HCMA1104-1R0-R



Inductance characteristics



Solder reflow profile




Table 1 - Standard SnPb Solder (T_C)

Package Thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5mm)	235°C	220°C
≥2.5mm	220°C	220°C

Table 2 - Lead (Pb) Free Solder (T_C)

Package Thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6mm	260°C	260°C	260°C
1.6 – 2.5mm	260°C	250°C	245°C
>2.5mm	250°C	245°C	245°C

Reference JDEC J-STD-020

Profile Feature	Standard SnPb Solder	Lead (Pb) Free Solder
Preheat and Soak	<ul style="list-style-type: none"> Temperature min. (T_{smin}) Temperature max. (T_{smax}) Time (T_{smin} to T_{smax}) (t_s) 	<ul style="list-style-type: none"> 100°C 150°C 60-120 Seconds
Average ramp up rate T _{smax} to T _p	3°C/ Second Max.	3°C/ Second Max.
Liquidous temperature (T _L)	183°C	217°C
Time at liquidous (t _L)	60-150 Seconds	60-150 Seconds
Peak package body temperature (T _p)*	Table 1	Table 2
Time (t _p)** within 5 °C of the specified classification temperature (T _C)	20 Seconds**	30 Seconds**
Average ramp-down rate (T _p to T _{smax})	6°C/ Second Max.	6°C/ Second Max.
Time 25°C to Peak Temperature	6 Minutes Max.	8 Minutes Max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.
 ** Tolerance for time at peak profile temperature (t_p) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
 1000 Eaton Boulevard
 Cleveland, OH 44122
 United States
www.eaton.com/electronics

© 2018 Eaton
 All Rights Reserved
 Printed in USA
 Publication No. 10349 BU-SB14815
 August 2018

Eaton is a registered trademark.
 All other trademarks are property of their respective owners.