

Specification Sheet

Part Number: TELS-27



Continuous strap and separate heads allow for any bundle diameter, eliminating waste.
Smooth strap prevents cable damage.
UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

Extended-Length Tie, POM, Black, 10-27" straps and 10 heads/Kit

Article Number	111-32110
Type	TELS-27
Color	Black (BK)
Quantity Per	pack
Product Description	Extended Length Ties provide a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls provide a strong grip on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.
Short Description	Extended-Length Tie, POM, Black, 10-27" straps and 10 heads/Kit

Global Part Name	TELS-27-POM-BK
-------------------------	----------------

Minimum Tensile Strength (Imperial)	250.0
--	-------

Minimum Tensile Strength (Metric)	1115.0
--	--------

Length L (Imperial)	27.0
----------------------------	------

Length L (Metric)	686.0
--------------------------	-------

Fixation Method	2 piece
------------------------	---------

Identification Plate Position	none
--------------------------------------	------

Releasable Closure	No
---------------------------	----

Tie Closure	steel pawl
--------------------	------------

Variant	Extended Length
----------------	-----------------

Width W (Imperial)	0.5
---------------------------	-----

Width W (Metric)	12.7
-------------------------	------

Thickness T (Imperial)	0.06
-------------------------------	------

Thickness T (Metric)	1.52
-----------------------------	------

Height H (Imperial)	.49
----------------------------	-----

Height H (Metric)	12.40
--------------------------	-------

Material	Polyacetal (POM)
Material Shortcut	POM
Material Cable Tie	Polyacetal (POM)
Material Head	Polyacetal (POM)
Flammability	UL 94 HB
Operating Temperature	-40°F to +194°F (-40°C to +90°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	10
Package Quantity (Metric)	10
Customs Number	3926909988