
ADELS contact

Screw-Screwless Connectors

900 Q/ 5



terminal block, 5 pole, fixing: screw, clamping units per pole: 4, voltage rating: 450 V, current rating: 17.5 A, cross-section rating external: 2.5 mm², cross-section rating internal: 1.5 mm²

Order Info

reference number (ref. no.)	114005
PU	500
EAN	4028012104345

Type

type	terminal block
number of poles	5 pole
clamping units per pole	4
colour	white
cross-section rating	1.5 / 2.5 mm²
connection type	screw-screwless

Technical Data

voltage rating	450 V
current rating	17.5 A
insulating material	PA 6.6
contact material	brass
flammability rating	V-2
max. Ambient Temperature Operation	85 °C
Assembly Contact Screw	0.8x4.0 / ↻ 0.5 Nm
internal core cross-section max.	1.5 mm²
internal stripping length	7.0-7.5 mm
external stripping length	8.0-8.5 mm
fixing	screw
internal core cross-section min.	0.5 mm²
Type of Conductor Solid External	yes
Type of Conductor Flexible External	yes
Type of Conductor Solid Internal	yes
Type of Conductor Stranded Internal	yes
cross-section rating external	2.5 mm²
cross-section rating internal	1.5 mm²

Approvals

acc. to EN 60998	Download PDF
acc. to UL	Download PDF
acc. to CSA	Download PDF

Accessories

ZEL 110	196420