HellermannTyton

Specification Sheet

Part Number: TAG27-400

Tabtag dot matrix labels are specifically made for use in dot matrix printers for fast and easy printing.

Labels come with a pin-feed margin to ensure they can easily be loaded into any dot matrix printing system.

White dot matrix polyester has a matte finish, allowing for the highest resolution and print contrast using impact printers.



The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Article Number 595-27400

Type TAG27

Color White (WH)

Quantity Per pack

Product Description

HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 400 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.

| Short Description | Dot Matrix Label, 0.75" x 1.5", 1 Across, Polyester, White, 5000/pkg |
|--------------------------------|--|
| Global Part Name | TAG27-400-WH |
| | |
| Width W (Imperial) | 0.75 |
| Width W (Metric) | 19.05 |
| Bundle Diameter Min (Imperial) | .24 |
| Bundle Diameter Min (Metric) | 6.10 |
| Thickness T (Metric) | 25.0 |
| Height H (Imperial) | 1.5 |
| Height H (Metric) | 38.1 |
| Width of Liner (Metric) | 193.70 |
| Width of Liner (Imperial) | 7.625 |

Material Type 400, Polyester, white (400)

Material Shortcut 400

Adhesive Acrylic

Halogen Free No

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Operating Temperature -40°F to +302°F (-40°C to +150°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Certification/Specification **UL-Recognized**

UL Recognized (US) Yes

Package Quantity (Imperial) 5000

Package Quantity (Metric) 5000

Customs Number 3919905060

Labels per Column 1

Labels per Row 1