


## Specification Sheet

Part Number: 553-50027

Slide Slit and optional center slits for easy wire insertion.  
Smooth surface for clean and legible printing.

Supplied on a ladder style carrier so that markers can be kitted after printing.

A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.



ShrinkTrak Labels, 1-Sided, 1-Slit, .38" (9.52mm), PO-X, Yellow, 500/box

**Article Number** 553-50027

**Type** HST9-3YE-S

**Color** Yellow (YE)

**Quantity Per** box

**Product Description** HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

**Short Description** ShrinkTrak Labels, 1-Sided, 1-Slit, .38" (9.52mm), PO-X, Yellow, 500/box

**Global Part Name** HST9-3YE-S-PO-X-YE

**Variant** Thin-Wall

**Width W (Imperial)** 0.95

**Width W (Metric)** 24.13

**Thickness T (Imperial)** .003

**Thickness T (Metric)** .0762

**Height H (Imperial)** 0.597

**Height H (Metric)** 15.16

**Width of Liner (Metric)** 76.2

**Width of Liner (Imperial)** 3.0

**Outside Diameter OD (Imperial)** 0.375

**Outside Diameter OD (Metric)** 9.52

**Outside Diameter Max (Imperial)** 0.375

**Outside Diameter Max (Metric)** 9.52

**Wall Thickness WT (Imperial)** 0.031

**Wall Thickness WT (Metric)** 0.79

<b>Material</b>	Polyolefin, cross-linked (PO-X)
<b>Material Shortcut</b>	PO-X
<b>US MIL SPEC</b>	MIL-STD-202G Method 215K SAE-AS81531 SAE-AMS-DTL-23053/5 Class 1 and 3
<b>Flammability</b>	UL 224 VW-1
<b>Halogen Free</b>	No
<b>Operating Temperature</b>	-67°F to +275°F (-55°C to +135°C)
<b>Reach Compliant (Article 33)</b>	Yes
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL 224 125 °C 600V VW-1 SAE - AS81531 SAE - AMS - DTL-23053/5 Class 1 and 3
<b>Package Quantity (Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3917320000
<b>Labels per Column</b>	1

