

Specification Sheet

Part Number: TM1SF9M4



Push Mounts, when used with standard cable ties, provide a permanent bundling solution.

The low profile style head is ideal for space constrained areas and is easily inserted through a pre-drilled hole.

Push-Button Cable Tie Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, Natural, 1000/pkg

Article Number 151-40103

Type TM1SF

Color Natural (NA)

Quantity Per bag

Product Description HellermannTyton push mounts are used with our standard cable ties and offer a permanent bundling solution for quick installation by pushing the mount through a pre-drilled hole. The low profile head is suitable in space constrained areas.

Short Description Push-Button Cable Tie Mount, .25" Hole Dia, .13" Max Panel, .2" Max Tie Width, PA66, Natural, 1000/pkg

Global Part Name TM1SF-PA66-NA

| | |
|--|--------------------------------------|
| Length L (Imperial) | 0.62 |
| Length L (Metric) | 15.75 |
| Fixation Method | with Arrowhead / Push Mount (Mounts) |
| Width W (Imperial) | 0.4 |
| Width W (Metric) | 10.2 |
| Cable Ties | T18 - T50 |
| Height H (Imperial) | .18 |
| Height H (Metric) | 4.60 |
| Cable Tie Width Max (Imperial) | 0.2 |
| Cable Tie Width Max (Metric) | 5.0 |
| Panel Thickness Min (Imperial) | 0.13 |
| Panel Thickness Max (Imperial) | 0.13 |
| Panel Thickness Min (Metric) | 3.40 |
| Panel Thickness Max (Metric) | 3.3 |
| Mounting Hole Diameter D (Imperial) | 0.25 |
| Mounting Hole Diameter D (Metric) | 6.35 mm |

Mounting Hole Diameter D Max (Metric) 6.35

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL 94 V-2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3926909988