

Specification Sheet

Part Number: T150XL3X2



Engineered and manufactured for maximum performance and quality
Made from 100% high-quality plastic to ensure efficient recycling

Inside serration for a strong grip onto bundles

Easy application either manually or with a processing tool

Heavy Duty Cable Tie, 43" Long, UL Rated, 175lb Tensile Strength, PA66, Orange, 25/pkg

Article Number	111-15504
Type	T150XL
Color	Orange (OG)
Quantity Per	bag
Product Description	Heavy duty T-Series cable ties feature inside serrations to provide a positive hold on wire and cable bundles. Durable head design guarantees high tensile strength and a low insertion force. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Heavy Duty Cable Tie, 43" Long, UL Rated, 175lb Tensile Strength, PA66, Orange, 25/pkg

Global Part Name	T150XL-PA66-OG
-------------------------	----------------

Minimum Tensile Strength (Imperial)	175.0
--	-------

Minimum Tensile Strength (Metric)	780.0
--	-------

Length L (Imperial)	43.0
----------------------------	------

Length L (Metric)	1095.0
--------------------------	--------

Identification Plate Position	none
--------------------------------------	------

Releasable Closure	No
---------------------------	----

Tie Closure	plastic pawl
--------------------	--------------

Variant	Inside Serrated
----------------	-----------------

Width W (Imperial)	0.35
---------------------------	------

Width W (Metric)	8.9
-------------------------	-----

Bundle Diameter Min (Imperial)	6.0
---------------------------------------	-----

Bundle Diameter Min (Metric)	152.0
-------------------------------------	-------

Bundle Diameter Max (Imperial)	13.0
---------------------------------------	------

Bundle Diameter Max (Metric)	330.0
-------------------------------------	-------

Thickness T (Metric)	2.1
-----------------------------	-----

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Flammability	UL 94 V-2
Halogen Free	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	UL-ZODZ2.E64139
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	25
Package Quantity (Metric)	25
Customs Number	3926909988

