

## **Specification Sheet**

Part Number: 596-00827

Pre-Printed Vinyl Solar Labels are made with UV-stable inks and

materials for durability and weather resistance.

Supplied with an aggressive adhesive to ensure long life.

Meets NEC & IFC standards for printed text, character height, color and

outdoor UV stability to pass inspections.



Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.

Solar Label, Spanish, CAUTION PHOTOVOLTAIC SYSTEM BACKFED, 4.12" x .75", VL, Yellow, 50/roll

Article Number 596-00827

Type CBACKFEDS

Color Yellow (YE)

Quantity Per roll

Product Description HellermannTyton

HellermannTyton pre-printed Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description	Solar Label, Spanish, CAUTION PHOTOVOLTAIC SYSTEM BACKFED, 4.12" x .75", VL, Yellow, 50/roll
Global Part Name	CBACKFEDS-443/281-YE
Technical Description	Pre-Printed Solar Label, Spanish Version, "CAUTION - PV SYSTEM BACKFED", 4.125" X .75", Yellow
Local Order Number 2	English Version: 596-00587
Width W (Imperial)	4.125
Width W (Metric)	104.6
Thickness T (Imperial)	0.0025
Thickness T (Metric)	64.0
Height H (Imperial)	0.75
Height H (Metric)	19.05
Material	Type 443/281, UV-stabilized flexible white vinyl with clear polyester laminate (443/281)

443/281

Acrylic

**Material Shortcut** 

Adhesive

**Halogen Free** No **Adhesive Operating Temperature** -40°F to +174°F (-40°C to +79°C) **Operating Temperature** -40°F to +174°F (-40°C to +79°C) Reach Compliant (Article 33) Yes **ROHS Compliant** Yes Certification/Specification NEC2017 UL 969 NEC2020 NEC2014 **UL Recognized (US)** Yes Package Quantity (Imperial) 50 **Package Quantity (Metric)** 50 **Customs Number** 3919102055 Labels per Column 1

1

Labels per Row