

Specification Sheet

Part Number: DCT90HIRK2



Provides dual separation between bundles to prevent chafing and abrasion.
150lb. tensile strength ensures enough strength for heavy duty applications.
Straps are releasable for increased serviceability.

Dual Clamp Tie, 0.25" Stud Dia, 1.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black 50/pkg

Article Number	115-30900
Type	DCT9
Color	Black (BK)
Quantity Per	bag
Product Description	Dual-Clamp Ties are designed to provide parallel separation between hoses, wires, cables, and tubing to protect them from abrasion. These ties have an optional mounting hole for securing bundles along the chassis of trucks, trailers, and heavy-duty equipment. The unique one-piece design features the dual head centered on the strap.
Short Description	Dual Clamp Tie, 0.25" Stud Dia, 1.30" Max Bundle Dia, 150lb, PA66HIRHSUV, Black 50/pkg

Global Part Name	DCT9-PA66HIRHSUV-BK
------------------	---------------------

Minimum Tensile Strength (Imperial)	150.0
-------------------------------------	-------

Minimum Tensile Strength (Metric)	667.0
-----------------------------------	-------

Length L (Imperial)	13.0
---------------------	------

Length L (Metric)	331.0
-------------------	-------

Fixation Method	Weld Stud Fixing
-----------------	------------------

Identification Plate Position	none
-------------------------------	------

Releasable Closure	No
--------------------	----

Tie Closure	plastic pawl
-------------	--------------

Variant	Inside Serrated
---------	-----------------

Width W (Imperial)	0.504
--------------------	-------

Width W (Metric)	12.8
------------------	------

Bundle Diameter Min (Imperial)	0.25
--------------------------------	------

Bundle Diameter Min (Metric)	6.4
------------------------------	-----

Bundle Diameter Max (Imperial)	1.3
--------------------------------	-----

Bundle Diameter Max (Metric)	33.0
------------------------------	------

Height H (Imperial)	0.8
Height H (Metric)	20.32
Stud Diameter (Metric)	M6
Stud Diameter (Imperial)	1/4
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL 94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes
Package Quantity (Imperial)	50
Package Quantity (Metric)	50
Customs Number	3926909988

