

## EVA-SS

~15° smooth spot beam. Assembly with holder and installation tape.

### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 37.7 mm
Height	17.2 mm
Fastening	tape, pin
ROHS compliant	yes ⓘ


### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
EVA-SS	Single lens	PMMA	clear	
EVA-HLD-PIN	Holder	PC	black	
SPUTNIK-TAPE3	Tape	Acrylic foam	black	

### ORDERING INFORMATION:

Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CA16256_EVA-SS	Single lens	675	90	45	10.0
» Box size: 480 x 280 x 300 mm					






See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

### PHOTOMETRIC DATA (MEASURED):



#### CREE → LED

LED XHP35 HD  
 FWHM / FWTM 14.0° / 25.0°  
 Efficiency 92 %  
 Peak intensity 18 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:





#### CREE → LED

LED XHP35 HI  
 FWHM / FWTM 10.0° / 19.0°  
 Efficiency 93 %  
 Peak intensity 22 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### CREE → LED

LED XP-E  
 FWHM / FWTM 6.0° / 13.0°  
 Efficiency 93 %  
 Peak intensity 53.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:











#### CREE → LED

LED XP-G2  
 FWHM / FWTM 8.0° / 17.0°  
 Efficiency 93 %  
 Peak intensity 30 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (MEASURED):


<p><b>CREE</b> LED</p> <p>LED: XP-L HI            FWHM / FWTM: 8.0° / 15.0°            Efficiency: 93 %            Peak intensity: 34.2 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>		
<p><b>CREE</b> LED</p> <p>LED: XT-E            FWHM / FWTM: 8.0° / 17.0°            Efficiency: 91 %            Peak intensity: 29 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>		
<p><b>LUMILEDS</b></p> <p>LED: LUXEON CZ            FWHM / FWTM: 4.0° / 9.0°            Efficiency: 94 %            Peak intensity: 99.8 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>		
<p><b>LUMILEDS</b></p> <p>LED: LUXEON V            FWHM / FWTM: 13.0° / 23.0°            Efficiency: 91 %            Peak intensity: 14 cd/lm            LEDs/each optic: 1            Light colour: White            Required components:</p>		



### PHOTOMETRIC DATA (MEASURED):


#### LUMILEDS

LED LUXEON V2  
 FWHM / FWTM 9.0° / 17.0°  
 Efficiency 92 %  
 Peak intensity 26.6 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### NICHIA



LED NVSW219F  
 FWHM / FWTM 10.0° / 19.0°  
 Efficiency 92 %  
 Peak intensity 22.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### OSRAM

Opto Semiconductors


LED OSCONIQ P 3737 (2W version)  
 FWHM / FWTM 8.0° / 15.0°  
 Efficiency 94 %  
 Peak intensity 33.3 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### OSRAM

Opto Semiconductors

LED OSLON Black Flat  
 FWHM / FWTM 4.0° / 9.0°  
 Efficiency 94 %  
 Peak intensity 94 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### PHOTOMETRIC DATA (MEASURED):

#### OSRAM

Opto Semiconductors



LED OSLON Square CSSRM2/CSSRM3  
 FWHM / FWTM 8.0° / 16.0°  
 Efficiency 92 %  
 Peak intensity 32 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### OSRAM

Opto Semiconductors


LED OSLON Square EC  
 FWHM / FWTM 8.0° / 15.0°  
 Efficiency 91 %  
 Peak intensity 33.9 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### OSRAM


Opto Semiconductors

LED OSLON SSL 150  
 FWHM / FWTM 5.0° / 12.0°  
 Efficiency 93 %  
 Peak intensity 63 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### SAMSUNG



LED LH181A  
 FWHM / FWTM 7.0° / 16.0°  
 Efficiency 87 %  
 Peak intensity 28.2 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### PHOTOMETRIC DATA (MEASURED):



### SAMSUNG

LED LH181B  
 FWHM / FWTM 7.8° / 16.0°  
 Efficiency 92 %  
 Peak intensity 31 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




### SAMSUNG

LED LH351B  
 FWHM / FWTM 10.0° / 18.0°  
 Efficiency 93 %  
 Peak intensity 24.3 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



SEOUL SEMICONDUCTOR


LED nPola  
 FWHM / FWTM 5.0° / 9.0°  
 Efficiency 94 %  
 Peak intensity 94 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### PHOTOMETRIC DATA (SIMULATED):


#### CREE LED

LED XHP50.2  
 FWHM / FWTM 20.0° / 34.0°  
 Efficiency 90 %  
 Peak intensity 6.5 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




#### CREE LED

LED XP-E2  
 FWHM / FWTM 8.0° / 16.0°  
 Efficiency 93 %  
 Peak intensity 34.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



#### LUMILEDS

LED LUXEON MZ  
 FWHM / FWTM 14.0° / 24.0°  
 Efficiency 94 %  
 Peak intensity 13.4 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)