

## LXP3-RS2

~8.5° spot beam optimized for CREE XP-E. 14.7 mm high assembly.

### TECHNICAL SPECIFICATIONS:

Dimensions	Ø 21.6 mm
Height	14.7 mm
Fastening	glue
ROHS compliant	yes ⓘ




### MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
LXP2-RS2	Single lens	PMMA		
LXP3-LH1-WHT	Holder	PC	white	









### ORDERING INFORMATION:

Component	Type	Qty in box	MOQ	MPQ	Box weight (kg)
CP12817_LXP3-RS2	Single lens	1680	336	112	8.9
» Box size: 480 x 280 x 300 mm					







See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)

#### PHOTOMETRIC DATA (MEASURED):

<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED            XP-E            FWHM / FWTM    6.0° / 14.0°            Efficiency        94 %            Peak intensity    39.4 cd/lm            LEDs/each optic    1            Light colour      White            Required components:</p>		
<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED            XP-E2            FWHM / FWTM    6.0° / 14.0°            Efficiency        94 %            Peak intensity    40 cd/lm            LEDs/each optic    1            Light colour      White            Required components:</p>		
<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED            XP-G2            FWHM / FWTM    9.0° / 19.0°            Efficiency        94 %            Peak intensity    21 cd/lm            LEDs/each optic    1            Light colour      White            Required components:</p>		
<p><b>CREE</b> ⇄ <b>LED</b></p> <p>LED            XP-L HI            FWHM / FWTM    8.0° / 19.0°            Efficiency        93 %            Peak intensity    20 cd/lm            LEDs/each optic    1            Light colour      White            Required components:</p>		

#### PHOTOMETRIC DATA (MEASURED):

<p><b>CREE</b> LED</p> <p>LED XT-E            FWHM / FWTM 10.0° / 22.0°            Efficiency 94 %            Peak intensity 15.4 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		
<p><b>TOSHIBA</b>            Leading Innovation &gt;&gt;&gt;</p> <p>LED TL1L4            FWHM / FWTM 8.0° / 21.0°            Efficiency 94 %            Peak intensity 18 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>		

### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)