



CONSTRUCTION

Signal Conductor: 0.287+/-0.0025mm (0.0113+/-0.0001"), Silver Plated Copper per ASTM B-298
 Insulation: PFA per applicable paragraph MIL-DTL-17, 0.92+/-0.025mm (0.0363+/-0.001") OD
 Inner Shield: Helically Overlapped Flat Silver Plated Copper per ASTM B-298
 Braid Shield: 46 AWG Silver Plated Copper per ASTM B-298, >89% Coverage Ref.
 Overall Shield Diameter: 1.168+/-0.05mm (0.046+/-0.002")
 Jacket: FEP in accordance with MIL-DTL-17, Type IX
 Wall Thickness: 0.127mm (0.005")
 Color: Blue

ELECTRICAL

Impedance: 50+/-1 ohms
 Velocity Of Propagation: 70% Ref.
 Capacitance: 29 pF/ft (95 pF/m) Ref.

GENERAL

Temperature Rating: -65C to 150C (200C Static) Ref.
 Static Bend Radius: 5.0mm (0.2") Ref.
 Dynamic Bend Radius: 10.0mm (0.4") Ref.
 Weight: 3.5 lbs/1000ft Ref.

Frequency (GHz)	Attenuation (dB/100ft)
0.5	23.37
1.0	33.54
2	48.41
4	70.42
8	103.50
12	130.43
18	165.27
26	205.90
34	242.57
40	268.31
50	308.79
Att.=K1*SQRT(F MHz)+K2*F MHz	
K1=1.008	K2=0.00167

This document is the property of TEMP-FLEX. If may not be disclosed, reproduced, or otherwise used without permission.	Rev	DCR	Description	App'd	Date
	A	4019	Update Primary Insulation P/N.	KP	9/10/14
	B	4634	Update Dimensions, Opt. Temp., Add Attenuation Chart	KP	9/1/15