Zero Smog 4V Kit 1 Funnel

Product no.: T0053662299N



Benefits

- Equipped with HEPA H13 particle filter and fine dust pre-filter F7
- Constant Flow Control (CFC) guarantees automatic air flow regulation for each working place independent of the connected workplaces
- Electronic filter control with optical and acoustical filter alarm
- Low noise emission levels for quiet workspace
- RS232 port, can be remotely controlled via remote control (optional accessory) or by a PC with RS232 connection
- > Efficiency test via USB port
- 4 casters to allow easy movement of the unit
- > For connection to a WX / WT station a T0058768767 WT Hub is needed



| Dimensions L x W x H (mm) | 345 x 325 x 505 |
|----------------------------------|---|
| Dimensions L x W x H (inches) | 13,58 x 12,79 x 19,88 |
| Weight (approx.) in kg | 19 |
| Voltage | |
| Power | 275 VA |
| Noise level (distance 1 m) dB(A) | |
| Max. vacuum | |
| Capacity m³/h | 230 |
| Pre-filter | |
| Compact filter | Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Chemisorb) |
| Max. capacity | 1–4 workstations |
| RS232 interface (remote control) | All system functions can be operated and remotely monitored via the RS232 port. |
| USB port | on |
| WX-compatible | on |
| | |

Phone: +49 (0) 7143 / 580-0 Fax.: +49 (0) 7143 / 580-108 Email: info@weller-tools.com

Web: www.weller-tools.com