


Specifications:
Current rating:1.0A AC,DC
Voltage rating:50V AC, DC
Contact tesistance:20m ohm Max
Insulation resistance:1,000M ohm Min
Withstanding voltage:500V AC/minute
Operating Temperature:−40°C ~ +105°C

Materials:
Insulator:Nylon 9T(UL94V−0)
Standard Color:Black
Terminal:Brass
Finish:Gold Plated




PCB Layout


Dimension Information:

Pin.No	Dim.A	Dim.B	Dim.C	Pin.No	Dim.A	Dim.B	Dim.C
8	3.81	9.83	11.43	30	17.78	23.80	25.40
10	5.08	11.10	12.70	34	20.32	26.34	27.94
12	6.35	12.37	13.97	40	24.13	30.15	31.75
14	7.62	13.64	15.24	44	26.67	32.69	34.29
16	8.89	14.91	16.51	50	30.48	36.50	38.10
20	11.43	17.45	19.05	60	36.83	42.85	44.45
24	13.97	19.99	21.59	68	41.91	47.93	49.53
26	15.24	21.26	22.86				

MATING PART
3230−XX−0103−00



MATING PART
3230−XX−0104−00



RoHS Compliant

REV	DATE	FILE	BY
	05−FEB−2020		

DRAWN: Jamie
CHECKED: Jerry
APPROVAL: Rory

GENERAL TOLERANCE:
.X=±0.25
.XX=±0.20

UNIT: MM
SCALE:1:1
SHEET: 1 / 1
PROJECTION:

CnC Tech
Industrial Cable and Connector Technology

DESCRIPTION:
1.27mm Box Header SMT Type

PART NO:
3221-XX-0300-00

SIZE
A4