

REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A3	-	RELEASE NEW DWG FORMAT	03/JAN/14	ORION			
A4	-	ADD COLOR OPTION	23/NOV/20	LOUIE	TOMMY		







NOTES: UNLESS OTHERWISE SPECIFIED

1. MATERIAL: HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. MODIFICATIONS: BLOCKED GROMMET

3. SPECIFICATIONS:

- 3.1 CURRENT RATING: 13 AMPS 3.2 OPERATING TEMPERATURE: -55°C TO +125°C 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2
- MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.


3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.

- 3.5 MOISTURE RESISTANCE: IP68(1M OF WATER FOR A PERIOD OF 24 HOURS, MATED CONDITION) IP69K(MATED CONDITION)
- 3.6 MATING CYCLE DURABILITY: 100 CYCLES

3.7 RoHS COMPLIANT

MATING PART: AT06-3S* PLUG
(* = MODIFICATIONS AND COLORS)

5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



MPHENOL Ato4-3P

24.4

PART NUMBER CHART				
COLOR	PART NUMBER			
GREY	AT04-3P-SS01			
BLACK	AT04-3P-SS01BLK			
BLUE	AT04-3P-SS01BLU			
BROWN	AT04-3P-SS01BRN			
GREEN	AT04-3P-SS01GRN			
RED	AT04-3P-SS01RED			
WHITE	AT04-3P-SS01WHT			
YELLOW	AT04-3P-SS01YEL			
ORANGE	AT04-3P-SS01ORG			