



NOTES:
 1. SWITCH RATING: 1A, 125VAC, 30VDC
 UL, CSA
 2. CHARACTERISTICS MEASURED AT POINT "A".

REVISIONS		3TMT7084		REV. A
ECN	SYM	DESCRIPTION	DATE	BY
52424	A	CREATE NEW DRAWING	12-OCT-98	SUE

SWITCH CHARACTERISTICS	
OPERATE FORCE GRAMS	80 MAX
RELEASE FORCE GRAMS	16 MIN
RETURN FORCE GRAMS	9 MIN
DIFF MOTION MAX IN./MM	.032 / 0.813
PRETRAVEL MAX IN./MM	.200 / 5.080
OVERTRAVEL MIN IN./MM	.060 / 1.524

CAD FILE NO.: 3tmt7084_a

ALL DIMS. AND TOLS. PER ANS I Y14.5	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	3TMT7084	
THIS DOCUMENT AND THE INFORMATION IT CONTAINS IS THE EXCLUSIVE PROPERTY OF G&K COMPONENTS, INC., AND IS NOT TO BE USED OR DISCLOSED WITHOUT THE EXPRESS WRITTEN PERMISSION OF G&K COMPONENTS, INC.	TOLERANCES	DECIMAL .XXX ± .015 .XXX ± .005	
SCALE	DATE	SCALE	DATE
2:1	12-OCT-98	2:1	12-OCT-98
DRAWN	SUE	DRAWN	SUE
3TMT7084		3TMT7084	
SHT. NO. 1 OF 1		SHT. NO. 1 OF 1	