



Fork Board Lock Type

Directive 2002/95/EC  
RoHS  
Compliant

used for:

- Notes:
- Material And Finish
  - Shell: Steel, Nickel Plated
  - Bracket: Brass strip-H nickel plated
  - Screw: Brass nickel plated
  - Insulator-NYLDN 6T, UL-94V0, color black
  - PC 99: Colorful insulator
  - Pantone #661C: High Density 15 pos, Female
  - Contact: Phosphor bronze
  - Mating area: Gold plated
  - Sold Tails: Tin Plated

- Specifications
- Rated current: 5A max.
  - Rated Voltage: 300 VDC
  - Withstanding Voltage: 500 VAC (RMS) for 1 minute
  - Insulation Resistance: 1000 MΩm min. at 500 VDC
  - Contact Resistance: 13 mΩm max.
  - Dielectric Strength: 1000 VAC (RMS) for 1 minute
  - Temperature: -55 °C~+105 °C
- Operational Note:
- ①. Partmarking area to be degreased prior to marking operation

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION

<p>DO NOT ALTER CAD DRAWING BY HAND</p>		<p>tolerance unless otherwise specified</p>		<p>scale: material: SEE NOTES</p>	
<p>CONEC CORPORATION Brampton, Ontario</p>		<p>name date</p>		<p>drawing no.: AutoCAD 2004</p>	
<p>2004 drawn: [blank] date: [blank]</p>		<p>name date</p>		<p>part no.: 33DSMT1-E15SNCT</p>	
<p>appd: [blank] norm: [blank]</p>		<p>name date</p>		<p>AutoCAD 2004</p>	
<p>norm: [blank]</p>		<p>name date</p>		<p>A3</p>	
<p>q-oid: [blank]</p>		<p>name date</p>		<p>1/1</p>	
<p>rev: description</p>		<p>name date</p>		<p>DIN</p>	
<p>a origin</p>		<p>name date</p>		<p>sheet</p>	
<p>b RoHS May/14/07</p>		<p>name date</p>		<p>1/1</p>	
<p>c Javed</p>		<p>name date</p>		<p>1/1</p>	



D-Sub SMT 15 Female Connector

C0410DD03A

33DSMT1-E15SNCT