

D-subminiature parallel and serial cables

Ready-to-use cabling – call for custom lengths!**Features**

- Fully molded backshell with strain relief for added protection
- 26 AWG stranded conductors for flexibility
- Thumbscrews for tool-less termination
- All wired straight through except as noted

DB25 to DB25 – All pins terminated

Male to Female	Male to Male	Length	1-9	10-19	20-49	50-99	100+
232AMF5	232AMM5	1.8 m (6 ft)					
232AMF1	232AMM1	3.0 m (10 ft)					
232AMF15	—	4.6 m (15 ft)					
—	232AMM2	7.9 m (26 ft)					
232AMF2	—	7.9 m (26 ft)					

DB9 to DB9 – All pins terminated

Male to Female	Male to Male	Length	1-9	10-19	20-49	50-99	100+
9PAMF6	9PAMM6	1.8 m (6 ft)					
9PAMF10	9PAMM10	3.0 m (10 ft)					
9PAMF15	—	4.6 m (15 ft)					
9PAMF25	9PAMM25	7.9 m (26 ft)					

DB9 to DB25 adapter cable – 15.2 cm (6 in) cable converts 25-pin serial port to a 9-pin AT serial port

DB9 Male to DB25 Female	DB9 Female to DB25 Male	1-9	10-19	20-49	50-99	100+
232CAMR	232CAMS					

DB9 female to DB25 male modem cable – 9-wire, all pins terminated– PC-AT modem Cable

DB25 Male to DB9 Female	Length	1-9	10-19	20-49	50-99	100+
232CAM	1.8 m (6 ft)					
232CAM10	3.0 m (10 ft)					

9-pin null modem cable – Pins 2 and 3 crossed for RS-232 compliance – DB9 connectors on both ends

Female to Female	Male to Female	Length	1-9	10-19	20-49	50-99	100+
232NM9FF6	232NM9MF6	1.8 m (6 ft)					
232NM9	232NM9MF10	3.0 m (10 ft)					
232NM9FF25	232NM9MF25	7.9 m (26 ft)					

Port saver – Protect a highly used port from mechanical damage – Saves you from replacing an expensive card due to port damage

Model No.	Description	1-9	10-19	20-49	50-99	100+
9PSMF	Male to female DB9 port saver					
232PSMF	Male to female DB25 port saver					

USB Cables**High performance USB connectivity and USB extension****Features – USB cables**

- Connect your PC or device to any cable-less USB peripheral
- Type A male to Type B male
- Fully rated USB 2.0 peripheral cables

Features – USB extension cable

- This 3 meter extension cable extends a short cable on a USB peripheral to the full 5 meters length allowed (total cable length must not exceed 5 meters)
- Type A male to type A female



Model No.	Length	1-9	10-19	20-49	50-99	100+
USBAMBM-3F	3 ft (1m)					
USBAMBM-6F	6 ft (2m)					
USBAMBM-15F	15 ft (5m)					

Model No.	Length	1-9	10-19	20-49	50-99	100+
USBAMAF-10F	10 ft (3m)					