





Leiterplatten-Layout Vorschlag für SMT
PCB-Layout Proposal for SMT





Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating

Anschlussbereich verzinkt 4-6 µm
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
Coplanarity Area of Termination ≤ 0,1 mm

Verpackt in Gurtverpackung
Tape on Reel Packaging
Verpackungseinheit: 440 Stück
Packaging unit: 440 pcs



454197		weiß white	0,6	9	1,2	8,4	Codierung wie Variante schwarz Encoding such variant black
284124		rot red	4,2	5,4	4,8	4,8	
284123		grün green	3	6,6	3,6	6	
284122		blau blue	1,8	7,8	2,4	7,2	
284121		schwarz black	0,6	9	1,2	8,4	
Ident-Nr. part-no.	Codierung coding	Farbe color	A	B	C	D	Bemerkung note

Information:		Tolerances		Scale	3:1		
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation		M 2.54 SRC-A, 8-polig	
e		16.04.2013		ERNI		www.ERNI.com	224922
Index		Date		Class		SRCA	I A2