CZT4033

SURFACE MOUNT SILICON PNP TRANSISTOR



SOT-223 CASE

Central Semiconductor Corp.

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CZT4033 is a PNP silicon transistor manufactured by the epitaxial planar process, epoxy molded in a surface mount package, designed for high current general purpose amplifier applications.

MARKING: FULL PART NUMBER

MAXIMUM RATINGS: (T_A=25°C)	**SYMBOL**		**UNITS**
Collector-Base Voltage	V_{CBO}	80	V
Collector-Emitter Voltage	V_{CEO}	80	V
Emitter-Base Voltage	V_{EBO}	5.0	V
Continuous Collector Current	I_C	1.0	A
Peak Collector Current	I_{CM}	1.5	A
Power Dissipation	P_D	2.0	W
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	°C
Thermal Resistance	Θ_{JA}	62.5	°C/W

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)


SYMBOL	**TEST CONDITIONS**	**MIN**	**MAX**	**UNITS**
I_{CBO}	V_{CB}=60V		50	nA
I_{EBO}	V_{EB}=5.0V		10	nA
BV_{CBO}	I_C=10μA	80		V
BV_{CEO}	I_C=10mA	80		V
BV_{EBO}	I_E=10μA	5.0		V
$V_{CE(SAT)}$	I_C=150mA, I_B=15mA		0.15	V
$V_{CE(SAT)}$	I_C=500mA, I_B=50mA		0.50	V
$V_{BE(SAT)}$	I_C=150mA, I_B=15mA		0.90	V
$V_{BE(SAT)}$	I_C=500mA, I_B=50mA		1.10	V
h_{FE}	V_{CE}=5.0V, I_C=0.1mA	75		
h_{FE}	V_{CE}=5.0V, I_C=100mA	100	300	
h_{FE}	V_{CE}=5.0V, I_C=500mA	70		
h_{FE}	V_{CE}=5.0V, I_C=1.0A	25		
f_T	V_{CE}=10V, I_C=50mA, f=1.0MHz	100		MHz
C_{ob}	V_{CB}=10V, I_E=0, f=1.0MHz		20	pF
C_{ib}	V_{EB}=0.5V, I_C=0, f=1.0MHz		110	pF

R7 (9-May 2019)

CZT4033

SURFACE MOUNT SILICON
PNP TRANSISTOR

SOT-223 CASE - MECHANICAL OUTLINE



LEAD CODE:
1) Base
2) Collector
3) Emitter
4) Collector

MARKING:
FULL PART NUMBER

DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A	0°	10°	0°	10°
B	0.059	0.071	1.50	1.80
C	0.018	---	0.45	---
D	0.000	0.004	0.00	0.10
E	10°		10°	
F	0.009	0.014	0.23	0.35
G	0.248	0.270	6.30	6.85
H	0.114	0.122	2.90	3.10
I	0.130	0.146	3.30	3.70
J	0.264	0.287	6.70	7.30
K	0.024	0.033	0.60	0.85
L	0.091		2.30	
M	0.181		4.60	

SOT-223 (REV: R5)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centralsemi.com

Worldwide Field Representatives:
www.centralsemi.com/wwreps

Worldwide Distributors:
www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms