

Hinged Door Panels for DIN Subracks



VectorPak™ subrack hinged door panels screw directly into lower M2.5 tapped strip and secure at top M2.5 tapped strip with M2.5 captive screws. Doors can be added to any DIN subrack without exceeding 3U or 6U vertical height limitation. Aluminum doors are brushed aluminum with clear irridite finish. Polycarbonate doors are clear to light grey. Solid front or rear aluminum panels are 0.100"TH and attach to rack frame with M2.5 captive screws.

- VectorPak™ Hinged Front Door Front Panels for Subracks
- 84 HP Total Width (17.0") for all 19" DIN Subracks
- VectorPAK™ Solid Front/Rear Panels
- Solid 6061 Aluminum or Polycarbonate (0.100"TH)

| Part No. | Description |
|-----------|--|
| HFP3U-84 | 84HP door with captive screws & hinges, 3U, 6061 aluminum |
| HFP3UC-84 | 84HP door with captive screws & hinges, 3U, polycarbonate |
| HFP6U-84 | 84HP door with captive screws & hinges, 6U, 6061 aluminum |
| HFP6UC-84 | 84HP door with captive screws & hinges, 6U, 6061 polycarbonate |
| BP3U-84 | 84HP Solid Aluminum Front or Rear Panel, 3U or 6U |
| BP6U-84 | (attached with six M2.5 captive screw assemblies, included) |

Fan Trays & Accessories

19" Fan Trays



P/N FT1U-6



P/N FT1U-3

Vector fan trays are fully assembled, factory tested and fit into standard 19" racks. Fan trays feature solid state, brushless fan motors and include DC mating connector housing and pins. All electrical components and finger-guard covers are UL approved and recognized.

Filtered versions available

12 VDC Fan Tray Assemblies (Molex power connector, mating pins & housing included)

| Part No. | Air Speed (CFM) | Frequency | Noise dB (A) | Dimensions |
|----------|-----------------|-----------|--------------|------------------------------|
| FT1U-3 | 89 | 50/60Hz | 52 | 19.0" W X 1.72" H X 7.75" D |
| FT1U-6 | 89 | 50/60Hz | 52 | 19.0" W X 1.72" H X 12.95" D |
| FT1U-9 | 89 | 50/60Hz | 52 | 19.0" W X 1.72" H X 16.80" D |

115VAC Fan Tray Assemblies (includes power cord)

| Part No. | Air Speed (CFM) | Frequency | Noise dB (A) | Dimensions |
|----------|-----------------|-----------|--------------|------------------------------|
| FT1U-3AC | 70 | 50/60Hz | 52 | 19.0" W X 1.72" H X 7.75" D |
| FT1U-6AC | 70 | 50/60Hz | 52 | 19.0" W X 1.72" H X 12.95" D |
| FT1U-9AC | 70 | 50/60Hz | 52 | 19.0" W X 1.72" H X 16.80" D |