SBM2060VFCT

ULTRA LOW VF SCHOTTKY RECTIFIER

VOLTAGE	60 Volt	CURRENT	20 Ampere


FEATURES

- Ultra low forward voltage drop, low power loss
- High efficiency operation
- Lead free in compliance with EU RoHS 2011/65/EU directive
- Green molding compound as per IEC61249 Std. . (Halogen Free)

MECHANICAL DATA

- Case : ITO-220AB, Plastic
- Terminals : Solderable per MIL-STD-750, Method 2026
- Weight : 0.056 ounces, 1.6 grams.

ITO-220AB Unit : inch(mm)



MAXIMUM RATINGS(T_A=25°C unless otherwise noted)

PARAMETER		SYMBOL	VALUE	UNIT
Maximum repetitive peak reverse voltage		V_{RRM}	60	V
Maximum rms voltage		V_{RMS}	42	V
Maximum dc blocking voltage		V_R	60	V
Maximum average forward rectified current	per device per diode	$I_{F(AV)}$	20 10	A
Peak forward surge current : 8.3ms single half sine-wave superimposed on rated load	per diode	I_{FSM}	150	A
Typical junction capacitance (V_R=4V, f=1MHz)		C_J	480	pF
Typical thermal resistance per diode	(Note 1)	$R_{\Theta JC}$	15	°C/W
Operating junction temperature range		T_J	-55 to + 150	°C
Storage temperature range		T_{STG}	-55 to + 150	°C

Note : 1. Mounted on infinite heatsink.

SBM2060VFCT

ELECTRICAL CHARACTERISTICS(T_A=25°C unless otherwise noted)

PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT
Breakdown voltage per diode	V_{BR}	I_R=0.5mA		60	-	-	V
Instantaneous forward voltage per diode	V_F	I_F=3A I_F=5A I_F=10A	T_J=25°C	- - -	0.37 0.41 0.51	- - 0.57	V
		I_F=3A I_F=5A I_F=10A	T_J=125°C	- - -	0.31 0.38 -	- - -	V
Reverse current per diode	I_R	V_R=42V		-	45	-	μA
		V_R=60V	T_J=25°C T_J=125°C	- -	95 20	220 -	μA mA

SBM2060VFCT

Part No_packing code_Version

SBM2060VFCT_T0_00001

For example :

RB500V-40_R2_00001

Part No.

Serial number

Version code means HF

Packing size code means 13"

Packing type means T/R

Packing Code XX				Version Code XXXXX		
Packing type	1st Code	Packing size code	2nd Code	HF or RoHS	1st Code	2nd~5th Code
Tape and Ammunition Box (T/B)	A	N/A	0	HF	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			

SBM2060VFCT

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.