COAXIAL CABLE ASSEMBLY | CUSTOMER PRODUCT SPECIFICATION SHEET

RoHS Compliant


CAB467RF: I-PEX MHF 5L + RP FRONT MOUNT SMA S/T BULKHEAD JACK WITH O-RING RATED TO IP67/68 + Φ1.13MM CABLE, 6GHz


SPECIFICATIONS:
1. I-PEX MHF 5L PLUG, P/N: 20668-001R-13.
2. Φ1.13MM COAXIAL CABLE, COLOR: GRAY.
3. RP FRONT MOUNT SMA STRAIGHT BULKHEAD JACK WITH O-RING RATED TO IP67/68, P/N: RFCT-SMA088-F78.


ENVIRONMENTAL:
A. BULKHEAD MOUNTED CONNECTOR (RFCT-SMA088-F78) RATED TO THE FOLLOWING SPECIFICATION:
   i. IP6X - DUST TIGHT - NO PARTICLE INGRESS.
   ii. IPX7 WATERPROOF FOR 30 MINUTES UP TO 1 METER UNDERWATER.
   iii. IPX8 WATERPROOF FOR 48 HOURS AT 1 METER UNDERWATER.


NOTES:
1. THE ORIENTATION OF CONNECTORS ON DRAWING IS FOR REFERENCE ONLY, IF THE ORDER IS LEFT BLANK THE CONNECTOR WILL NOT HAVE FIXED ORIENTATION.
2. FIXED ORIENTATION IS SUGGESTED FOR CABLE LENGTH 25MM TO 100MM. PLEASE SPECIFY THE FIXED ORIENTATIONS FROM THE ORDER CODE (F1, F2, ETC)
3. CONTACT GRADCONN IF THE ORIENTATION YOU REQUIRE IS NOT SHOWN.
4. WORKING FREQUENCY RANGE: DC-6GHz.
5. OPERATING TEMPERATURE: -40°C~+85°C.
6. IMPEDANCE: 50 OHM.
7. IT IS INTENDED THAT MOUNTING OF THIS CONNECTOR IS ACHIEVED USING THE NUT AND WASHER PROVIDED. PLEASE CONTACT GRADCONN FOR ADVISE IF PLANNING TO USE A DIFFERENT METHOD OF MOUNTING.


USAGE PRECAUTIONS: CABLES USING 'MICRO' COAX ARE DELICATE:
(i) HANDLE WITH CARE.
(ii) DO NOT TWIST, APPLY EXCESSIVE FORCES OR SHARP BENDS TO THE CABLE. DO NOT FORCEFULLY DEFORM WIRES.
(iii) CONSULT CONNECTOR MANUFACTURER'S DATASHEETS FOR DETAILED NOTES ON HANDLING INSTRUCTIONS.











SMA DETAIL DRAWING

HOW TO ORDER


CAB467RF - XXXX - XX - X - 1


"L" LENGTH IN MM:
eg. 100MM = 0100
(MIN. 0050-MAX.0400
STANDARD = 0100, 1050, 0200)
Tolerance: 50-200mm: ±5mm.
201-400mm: ±7mm.

CABLE SIZE OPTION:
1 = Φ1.13MM CABLE, COLOR: GRAY

WASHER AND NUT OPTIONS:
BLANK = SEPARATELY PACKED (STANDARD)
A = ALL ASSEMBLED WITH CONNECTOR

ORIENTATION OPTIONS:
BLANK = DOES NOT HAVE A FIXED ORIENTATION
F1 = MHF CONNECTION DOWN (L=50-200MM)
F2 = MHF CONNECTION UP (L=50-200MM)
F3 = MHF CONNECTION AND D FLAT SAME ORIENTATION (L=50-200MM)
F4 = MHF CONNECTION AND D FLAT OPPOSITE ORIENTATION (L=50-200MM)
(SEE NOTES 1, 2, 3 AND DIAGRAMS FOR MORE INFORMATION)





RECOMMENDED SMA MOUNTING HOLE

REV	DATE & DRN
1.0	29/04/21 - NYW RELEASE

Scale: NTS	THIRD ANGLE	Unstated Tolerances: X N/A, .XX N/A, .XXX N/A, ANGLES N/A	Drawing Number: CAB467RF
Drawn: NYW			
App'd: XXX	Title: CABLE ASSEMBLY		Sheet 1 of 1
Date: 29 APR. '21	Revision: 1.0	Unit: mm	Drawing © E and O E

NAUTILUS IP67/68 Rated Cables

GRADCONN www.gradconn.com

© THIS DRAWING IS CONFIDENTIAL AND MUST NOT BE COPIED OR DISCLOSED WITHOUT WRITTEN CONSENT