

building a smarter, unified business foundation

UNITED STATES [CHANGE] ENGLISH REGISTER / LOG IN FOLLOW US



SOLUTIONS PRODUCTS AND SERVICES SUPPORT ABOUT US

Search Panduit.com Submi



Search within category

BUY NOW

DESIGN / INSTALL



LAM3B2-14-6Y

Two-hole, aluminum, three barrel lug, type LAM3B, NEMA hole sizes and spacing, #14 - #2 AWG, 1/4" (6.4mm) stud hole.
 LAM3B2-14-6Y replaces LAM3B2-14-6

Specs

★ Add to Favorites

🛒 Add to BOM

RoHS Compliancy Status	Compliant
Note	LAM3B2-14-6Y replaces LAM3B2-14-6
Product Type	Mechanical Connectors - Lugs
Material	Tin-Plated Aluminum
Height (mm)	11.9
Height (In.)	0.47
Length (mm)	63.2
Length (In.)	2.49
Stud Hole Size (In.)	1/4
Stud Hole Spacing (In.)	0.87
Tongue Width (In.)	1.63
Tongue Length	2.03
Aluminum or Copper Conductor Size Range	#14 AWG - #2 AWG
Figure No.	1
Tongue Thickness	0.19
CE Compliant	No
Tongue Length (mm)	51.6
Hex Key Size (In.)	**
Conductor Size Range (mm²)	2.5 - 35
Tightening Torque (In-Lbs)	50*
Tongue Type	Straight
Min. Order Qty.	1.0000