MMBT3906-AU

PNP GENERAL PURPOSE SWITCHING TRANSISTOR

VOLTAGE 40 Volt **POWER** 330 mWatt

SOT-23 Unit : inch(mm)



FEATURES

- PNP epitaxial silicon, planar design
- Collector-emitter voltage VCE = -40V
- Collector current IC = -200mA
- Lead free in compliance with EU RoHS 2.0
- Green molding compound as per IEC 61249 standard
- AEC-Q101 qualified

MECHANICAL DATA

Case: SOT-23, Plastic

Terminals: Solderable per MIL-STD-750, Method 2026

Approx. Weight: 0.0003 ounces, 0.0084 grams

Marking: S2A



ABSOLUTE RATINGS

Parameter	Symbol	Value	Units
Collector - Emitter Voltage	V_{CEO}	-40	V
Collector - Base Voltage	V_{CBO}	-40	V
Emitter - Base Voltage	V_{EBO}	-5	V
Collector Current - Continuous	I_C	-200	mA

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Units
Max Power Dissipation (Note 1)	P_{TOT}	330	mW
Thermal Resistance , Junction to Ambient	$R_{\theta JA}$	375	^{O}C/W
Operating Junction Temperature and Storage Temperature Range	T_J,T_{STG}	-55 to 150	^{O}C

Note 1: Transistor mounted on FR-5 board 1 x 0.75 x 0.062 in.

MMBT3906-AU

ELECTRICAL CHARACTERISTICS

Parameter	Symbol	Test Condition	MIN.	TYP.	MAX.	Units
Collector - Emitter Breakdown Voltage	$V_{(BR)CEO}$	IC=-1mA, IB=0	-40	-	-	V
Collector - Base Breakdown Voltage	$V_{(BR)CBO}$	IC=-10uA, IE=0	-40	-	-	V
Emitter - Base Breakdown Voltage	$V_{(BR)EBO}$	IE=-10uA, IC=0	-5	-	-	V
Base Cutoff Current	I_{BL}	VCE=-30V, VEB=-3V	-	-	-50	nA
Collector Cutoff Current	I_{CEX}	VCE=-30V, VEB=-3V	-	-	-50	nA
DC Current Gain (Note 2)	h_{FE}	IC=-0.1mA, VCE=-1V IC=-1mA, VCE=-1V IC=-10mA, VCE=-1V IC=-50mA, VCE=-1V IC=-100mA, VCE=-1V	60 80 100 60 30	- - - - -	- - 300 - -	-
Collector - Emitter Saturation Voltage (Note 2)	$V_{CE(SAT)}$	IC=-10mA, IB=-1mA IC=-50mA, IB=-5mA	-	-	-0.25 -0.4	V
Base - Emitter Saturation Voltage (Note 2)	$V_{BE(SAT)}$	IC=-10mA, IB=-1mA IC=-50mA, IB=-5mA	-0.65 -	- -	-0.85 -0.95	V
Collector - Base Capacitance	C_{CBO}	VCB=-5V, IE=0, f=1MHz	-	-	4.5	pF
Emitter - Base Capacitance	C_{EBO}	VEB=-0.5V, IC=0, f=1MHz	-	-	10	pF
Delay Time	td	V_{CC}=-3V,V_{BE}=-0.5V, I_C=-10mA,I_B=-1mA	-	-	35	ns
Rise Time	tr	V_{CC}=-3V,V_{BE}=-0.5V, I_C=-10mA,I_B=-1mA	-	-	35	ns
Storage Time	ts	VCC=-3V,IC=-10mA IB1=IB2=-1mA	-	-	225	ns
Fall Time	tf	VCC=-3V,IC=-10mA IB1=IB2=-1mA	-	-	75	ns
Current Gain-Bandwidth Product	f_T	I_C=-10mA,V_{CE}=-20V, f=100MHz	250	-	-	MHz

Note 2: Pulse Test: Pulse Width ≤ 300 us, Duty Cycle ≤ 2.0%.

SWITCHING TIME EQUIVALENT TEST CIRCUITS



Delay and Rise Time Equivalent Test Circuit



Storage and Fall Time Equivalent Test Circuit

ELECTRICAL CHARACTERISTICS CURVE



Fig. 1. Typical h_{FE} vs. Collector Current



Fig. 2. Typical V_{BE} vs. Collector Current



Fig. 3. Typical $V_{CE\ (sat)}$ vs. Collector Current



Fig. 4. Typical $V_{BE\ (sat)}$ vs. Collector Current



Fig. 5. Typical Capacitances vs. Reverse Voltage

MMBT3906-AU

MOUNTING PAD LAYOUT

SOT-23 Unit：inch(mm)



ORDER INFORMATION

- Packing information

  T/R - 12K per 13" plastic Reel

  T/R - 3K per 7" plastic Reel

MMBT3906-AU

Part No._packing code_Version

MMBT3906-AU_R1_000A1

MMBT3906-AU_R2_000A1

For example :

RB500V-40_R2_00001



Packing Code XX				Version Code X		Serial number XXXX
Packing type	1st Code	Packing size code	2nd Code	HSF Level	1st Code	2nd~5th Code
Tape and Ammunition Box (T/B)	A	N/A	0	Halogen free RoHS compliant	0	serial number
Tape and Reel (T/R)	R	7"	1	RoHS compliant	1	serial number
Bulk Packing (B/P)	B	13"	2			
Tube Packing (T/P)	T	26mm	X			
Tape and Reel (Right Oriented) (TRR)	S	52mm	Y			
Tape and Reel (Left Oriented) (TRL)	L	PANASERT T/B CATHODE UP (PBCU)	U			
FORMING	F	PANASERT T/B CATHODE DOWN (PBCD)	D			

MMBT3906-AU

Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.