



## 36W LED Driver with 3 Channel Constant Current Outputs PDA038B LED Power Supply



### Features

- 3 Channel Output
- OVP, OTP and Short-Circuit Protection
- Brownout Protection
- Class 2 Output per UL1310
- IP65 Rated
- AC input: 108-304VAC
- $\geq 0.9$  Power Factor Correction & THD <20%

### Applications

- Troffers

### Safety Approvals

- cUL/UL8750 / UL60950
- Class 2 Output per UL1310

### Mechanical Characteristics

- Length: 242mm (9.53in)
- Width: 43.5mm (1.71in)
- Height: 30.5mm (1.2in)
- Weight: 650g

### Output Specifications

#### Channel 1~3

| Model         | DC Output Voltage |      |      | Output Current | Output Power |
|---------------|-------------------|------|------|----------------|--------------|
|               | Min.              | Typ. | Max. |                |              |
| PDA038B-T350G | 27V               | -    | 36V  | 350mA          | 19W          |

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**INPUT:**

**AC Input Voltage Range**  
108~304VAC

**AC Input Voltage Rating**  
120~277VAC

**AC Input Frequency**  
47~63 Hz

**Maximum Input Current**  
≤ 0.5A

**Leakage Current**  
0.75mA maximum

**Power Factor**  
≥ 0.9

**THD**  
< 20%

**OUTPUT:**

**Output Current Ripple**  
≤ 60%

**Efficiency**  
83% at 120VAC  
84% at 277VAC  
Typical Efficiency: 86%

**Environmental:**

**Temperature**  
Operation Tc           -20 to 70°C  
Non-operation         -40 to +85°C  
Operating Humidity    5% to 95%

**EMC**

FCC Part 15B, Class A

**Immunity**

IEC61000-4-5

**Dielectric Withstand (Hi-pot) Test**

Primary to secondary: 3600VAC for 3 seconds, 10mA

**Insulation Resistance**

Primary to secondary: >5M Ohm 500VDC, 1 Minute

**Short-Circuit Protection**

Latch requires power cycle to restart

**Output Over-voltage Protection**

Max Voltage Limit 42V

**Input / Output Connections**

| Position | Terminal Color | Specification    | Length |
|----------|----------------|------------------|--------|
| Input    | Black          | AWG18 Solid Wire | 360mm  |
|          | White          | AWG18 Solid Wire | 360mm  |
|          | Green/Yellow   | AWG18 Solid Wire | 220mm  |
| Output   | Red(+)         | AWG18 Solid Wire | 200mm  |
|          | Blue(-)        | AWG18 Solid Wire | 200mm  |
|          | Blue(-)        | AWG18 Solid Wire | 200mm  |
|          | Blue(-)        | AWG18 Solid Wire | 200mm  |

**Warranty**

5 Years

