

## PushPull V4, compact housing w/o clip



•	
Part number	09 45 545 0043
Specification	PushPull V4, compact housing w/o clip
HARTING eCatalogue	https://b2b.harting.com/09455450043

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Connectors
Series	HARTING PushPull (V4)
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	Compact With integrated seal
Version	
Locking type	PushPull
Technical characteristics	
Limiting temperature	-40 +85 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP65 IP67
Vibration resistance	10-500 Hz, 5 g, 0.35 mm, 2h/axis 5.72 m/s² acc. to IEC 61373 Category 1 Class B
Shock resistance	25 g / 11 ms, 3 shocks / axis and direction 5 g / 30 ms, 5 shocks / axis and direction acc. to IEC 61373 Category 1 Class B
Material properties	
Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black

Colour (nood/nousing)	DIACK
Material (seal)	TPE-V
Material flammability class acc. to UL 94	V-0
RoHS	compliant

Page 1 / 2 | Creation date 2022-08-09 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



## Material properties

ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
Specifications and approvals	
Specifications	IEC 61076-3-106 Variant 4 (V4) EN 45545-2
UL / CSA	UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079
Commercial data	
Packaging size	1

Net weight	3.13 g
Country of origin	Romania
European customs tariff number	85366990
eCl@ss	27440202 Shell for industrial connectors