


Jul.1.2022 Copyright 2022 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
 In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD		MIL-STD-348B													
RATING	OPERATING TEMPERATURE RANGE	- 55° C TO + 105° C (95%RH MAX)	STORAGE TEMPERATURE RANGE	- 55° C TO + 50° C (95%RH MAX)											
	POWER	—W	CHARACTERISTIC IMPEDANCE	50 Ω (0 TO 40 GHz)											
	PECULIARITY	—	APPLICABLE CABLE	—											
SPECIFICATIONS															
ITEM	TEST METHOD		REQUIREMENTS		QT AT										
CONSTRUCTION															
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X X										
MARKING	CONFIRMED VISUALLY.				— —										
ELECTRIC CHARACTERISTICS															
CONTACT RESISTANCE	100 mA MAX (DC OR 1000 Hz).		CENTER CONTACT	4 mΩ MAX.	X X										
			OUTER CONTACT	2 mΩ MAX.	X X										
INSULATION RESISTANCE	500 V DC.		1000 MΩ MIN.		X X										
VOLTAGE PROOF	500 V AC FOR 1 min. CURRENT LEAKAGE 2mA MAX.		NO FLASHOVER OR BREAKDOWN.		X X										
VOLTAGE STANDING WAVE RATIO	FREQUENCY 0.04 TO 40 GHz		VSWR	1.10 MAX. (0.04 to 18 GHz)	X —										
	□> TEST METHOD IS Back to Back		VSWR	1.15 MAX. (18 to 26.5 GHz)											
			VSWR	1.30 MAX. (26.5 to 40 GHz)											
INSERTION LOSS	FREQUENCY — TO — GHz		— dB MAX.		— —										
MECHANICAL CHARACTERISTICS															
CONTACT INSERTION AND EXTRACTION FORCES	0 Φ0.9195 -0.0025 BY STEEL GAUGE.		INSERTION FORCE	— N MAX.	— —										
			EXTRACTION FORCE	0.4 N MIN.	X X										
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.		INSERTION FORCE	— N MAX.	— —										
			EXTRACTION FORCE	— N MIN.	— —										
MECHANICAL OPERATION	500 TIMES INSERTIONS AND EXTRACTIONS.		1) CONTACT RESISTANCE: CENTER CONTACT 6 mΩ MAX. CHANGE OUTER CONTACT 4 mΩ MAX. CHANGE 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X —										
VIBRATION	FREQUENCY 10 TO 2000 Hz SINGLE AMPLITUDE 0.75 mm, 196 m/s ² AT 12 CYCLES FOR 3 DIRECTIONS.		1) NO ELECTRICAL DISCONTINUITY OF 1 μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X —										
SHOCK	1960 m/s ² DIRECTIONS OF PULSE 6 ms AT 3 TIMES FOR 3 DIRECTIONS.				X —										
CABLE CLAMP ROBUSTNESS (AGAINST CABLE PULL)	APPLYING A PULL FORCE THE CABLE AXIALLY AT —N MAX.		1) NO WITHDRAWAL AND BREAKAGE OF CABLE. 2) NO BREAKAGE OF CLAMP.		— —										
ENVIRONMENTAL CHARACTERISTICS															
DAMP HEAT	EXPOSED AT -10 TO +65°C, 90 TO 98 % TOTAL 10 CYCLES (240h)		1) INSULATION RESISTANCE: 100 MΩ MIN. (AT HIGH HUMIDITY) 2) INSULATION RESISTANCE: 1000 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X —										
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55 → — → +105 → — °C TIME 30 → 3 → 30 → 3 min UNDER 5 CYCLES.		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X —										
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48h.		NO HEAVY CORROSION.		X —										
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 5%;">COUNT</th> <th style="width: 40%;">DESCRIPTION OF REVISIONS</th> <th style="width: 15%;">DESIGNED</th> <th style="width: 20%;">CHECKED</th> <th style="width: 20%;">DATE</th> </tr> </thead> <tbody> <tr> <td>△</td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>						COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE	△				
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE											
△															
REMARK			APPROVED	KY. SHIMIZU	15.10.22										
RoHS COMPLIANT			CHECKED	TO. KATAYAMA	15.10.22										
Note □> Measurement state of Back to Back.			DESIGNED	NK. OOSAWA	15.10.22										
Port1  Port2			DRAWN	NK. OOSAWA	15.10.22										
Unless otherwise specified, refer to MIL-STD-202.															
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-366760-11-00										
HRS	SPECIFICATION SHEET		PART NO.	HK-R-SR2-1 (11)											
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL338-0003-0-11	△ 1/1										