







THIS DOCUMENT IS THE PROPERTY OF KEYSTONE ELECTRONICS CORP. AND SHALL NOT BE REPRODUCED, DISTRIBUTED OR USED AS A BASIS FOR MANUFACTURE WITHOUT PRIOR WRITTEN PERMISSION FROM KEYSTONE ELECTRONICS CORP.

ACTUAL SIZE



- NOTE:**
1. INSULATION: MAT'L- NYLON 6T UL94V-0
 2. POST: MAT'L- BRASS FINISH TIN



- TAPE AND REEL SPECIFICATIONS:**
4. TAPE: MAT'L - ALL CONDUCTIVE POLYSTYRENE CARRIER ANSI/EIA-481 STANDARD
 5. REEL: 15.0 [380.8] DIA. 1000 PIECES PER REEL

KEYSTONE ELECTRONICS CORP.			
www.keyelco.com • NEW HYDE PARK, NY 11040 • Tel (516) 328-7500			
PART NAME			
SM SIDE ENTRY CONNECTOR (3 CIRCUITS)			
MATERIAL			
AS NOTED			
FINISH		DRN BY	DATE
AS NOTED		NT	3.07.16
		APP'D	SCALE
		RH	4X
TOLERANCES INCH [MM]		CODE	
DECIMAL $\pm .005$ [± 0.13]		DWG NO.	
ANGULAR $\pm 1^\circ$		976	
UNLESS OTHERWISE SPECIFIED			

6.18.21	CHANGE AS PER ECN 21-055	A
DATE	DESCRIPTION	REV.