SCOPE: DUAL POWER MOSFET DRIVER

Device Type	Generic Number	Circuit Function
01	MAX626M(x)/883B	Dual Power Inverting MOSFET Driver
02	MAX627M(x)/883B	Dual Power Noninverting MOSFET Driver
03	MAX628M(x)/883B	Dual Power Inverting/Noninverting MOSFET Driver
04	TSC426M(x)/883B	Dual Power Inverting MOSFET Driver
05	TSC427M(x)/883B	Dual Power Noninverting MOSFET Driver
06	TSC428M(x)/883B	Dual Power Inverting/Noninverting MOSFET Driver

Case Outline(s). The case outlines shall be designated in Mil-Std-1835 and as follows:

Outline Letter	Mil-Std-1835	Case Outline	Package Code
JA	GDIP1-T8 or CDIP2-T8	8 LEAD CERDIP	J8
NP	CQCC1-N20	20 Leadless Carrier	L20

Absolute Maximum Ratings

Supply Voltage V_{DD} to GND 20V
Input Voltage ..... V_{DD} +0.3V to GND -0.3V
Output Current (per pin, capacitive load) 1.5A
Peak Supply Current or GND Current (per pin) 3.0A

Lead Temperature (soldering, 10 seconds) ..... +300°C
Storage Temperature ..... -65°C to +150°C

Continuous Power Dissipation ..... T_A=+70°C
8 pin CERDIP(derate 8.0mW/°C above +70°C) 640mW
20 pin LCC(derate 9.1mW/°C above +70°C) 727mW
Junction Temperature T_J ..... +150°C
Thermal Resistance, Junction to Case, ΘJC
8 pin CERDIP..... 55°C/W
20 pin LCC ..... 20°C/W
Thermal Resistance, Junction to Ambient, ΘJA:
8 pin CERDIP..... 125°C/W
20 pin LCC ..... 110°C/W

Recommended Operating Conditions

Ambient Operating Range (T_A) ..... -55°C to +125°C
Supply Voltage Range ..... 4.5V≤V_{DD}≤18V

ORDERING INFORMATION:

Package	Device	Part #	Device	Part #
8 pin CERDIP	01	MAX626MJA/883B	04	TSC426MJA/883B
20 pin LCC	01	MAX626MNP/883B	04	TSC426MNP/883B
8 pin CERDIP	02	MAX627MJA/883B	05	TSC427MJA/883B
20 pin LCC	02	MAX627MNP/883B	05	TSC427MNP/883B
8 pin CERDIP	03	MAX628MJA/883B	06	TSC428MJA/883B
20 pin LCC	03	MAX628MNP/883B	06	TSC428MNP/883B

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TABLE 1. ELECTRICAL TESTS:

TEST	Symbol	CONDITIONS -55 °C <=T_A<= +125°C +4.5V≤V_{DD}≤18V Unless otherwise specified	Group A Subgroup	Device type	Limits Min	Limits Max	Units
Logic 1 Input Voltage	V_{IH}		1,2,3	All	2.4		V
Logic 0 Input Voltage	V_{IL}		1,2,3	All		0.8	V
Input Voltage Range	V_{IN}(max)		1,2,3	All	0	V_{DD}	V
Input Current	I_{IN}	V_{IN} =0V to 18V	1 2,3	All		±1 ±10	µA
Output High Voltage	V_{OH}	RL=∞	1,2,3	All	V_{DD}-25		mV
Output Low Voltage	V_{OL}	RL=∞	1,2,3	All		25	mV
Output Resistance	R_{OUT}	V_{DD}=18V, I_{OUT}=10mA NOTE 3, NOTE 4	1,2 3	All		20 15	Ω
Power Supply Current	I_{S1}	V_{IN}=+3V, both inputs	1,2 3	All		8 12	mA
Power Supply Current	I_{S2}	V_{IN}=0V, both inputs	1,2 3	All		0.4 0.6	mA
Rise Time	t_R	V_{DD}=18V NOTE 2	9 10,11 10,11	All 01,02,03 04,05,06		30 40 60	ns
Fall Time	t_F	V_{DD}=18V NOTE 2	9 10,11	All		30 40	ns
Delay Time	t_{D1}	V_{DD}=18V NOTE 2	9 10,11 9 10,11	01,02,03 04,05,06		30 40 40 60	ns
Delay Time	t_{D2}	V_{DD}=18V NOTE 2	9 10,11 9 10,11	01,02,03 04,05,06		50 75 60 120	ns

NOTE 1: Guaranteed by design.
NOTE 2: Subgroups 10 and 11 are guaranteed if not tested to the limits specified in Table 1.
NOTE 3: V_{IN}=0.8V for inverting stages, V_{IN}=2.4V for noninverting stages.
NOTE 4: V_{IN}=2.4V for inverting stages, V_{IN}=0.8V for noninverting stages.

TERMINAL CONNECTIONS FOR 01, 02, 03, 04, 05, 06

8 PIN CERDIP				20 PIN LCC							
	01,04	02,05	03,06		01,04	02,05	03,06		01,04	02,05	03,06
1	NC	NC	NC	1	NC	NC	NC	11	NC	NC	NC
2	INA	INA	INA	2	NC	NC	NC	12	NC	NC	NC
3	GND	GND	GND	3	NC	NC	NC	13	NC	NC	NC
4	INB	INB	INB	4	INA	INA	INA	14	$\overline{\text{OUTB}}$	OUTB	OUTB
5	$\overline{\text{OUTB}}$	OUTB	OUTB	5	NC	NC	NC	15	NC	NC	NC
6	V_{DD}	V_{DD}	V_{DD}	6	GND	GND	GND	16	V_{DD}	V_{DD}	V_{DD}
7	$\overline{\text{OUTA}}$	OUTA	$\overline{\text{OUTA}}$	7	NC	NC	NC	17	NC	NC	NC
8	NC	NC	NC	8	INB	INB	INB	18	$\overline{\text{OUTA}}$	OUTA	$\overline{\text{OUTA}}$
				9	NC	NC	NC	19	NC	NC	NC
				10	NC	NC	NC	20	NC	NC	NC

QUALITY ASSURANCE

Sampling and inspection procedures shall be in accordance with MIL-Prf-38535, Appendix A as specified in Mil-Std-883.

Screening shall be in accordance with Method 5004 of Mil-Std-883. Burn-in test Method 1015:

1. Test Condition, A, B, C, or D.
2. TA = +125°C minimum.
3. Interim and final electrical test requirements shall be specified in Table 2.

Quality conformance inspection shall be in accordance with Method 5005 of Mil-Std-883, including Groups A, B, C, and D inspection.

Group A inspection:

1. Tests as specified in Table 2.
2. Selected subgroups in Table 1, Method 5005 of Mil-Std-883 shall be omitted.

Group C and D inspections:

a. End-point electrical parameters shall be specified in Table 1.
b. Steady-state life test, Method 1005 of Mil-Std-883:
   1. Test condition A, B, C, D.
   2. TA = +125°C, minimum.
   3. Test duration, 1000 hours, except as permitted by Method 1005 of Mil-Std-883.

TABLE 2. ELECTRICAL TEST REQUIREMENTS

Mil-Std-883 Test Requirements	Subgroups per Method 5005, Table 1
Interim Electric Parameters Method 5004	1
Final Electrical Parameters Method 5005	1*, 2, 3, 9, 10**, 11**
Group A Test Requirements Method 5005	1, 2, 3, 9, 10**, 11**
Group C and D End-Point Electrical Parameters Method 5005	1

* PDA applies to Subgroup 1 only.
** Subgroups 10 and 11, if not tested, shall be guaranteed to the specified limits of Table 1.