CMPT5086
CMPT5086B
CMPT5087

SURFACE MOUNT SILICON PNP TRANSISTORS



SOT-23 CASE

Central Semiconductor Corp.

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMPT5086, CMPT5086B, and CMPT5087 are silicon PNP transistors manufactured by the epitaxial planar process, epoxy molded in a surface mount package, designed for applications requiring high gain and low noise.

MARKING CODES: **CMPT5086: C2P**
CMPT5086B: C2B
CMPT5087: C2Q

MAXIMUM RATINGS: (T_A=25°C)	**SYMBOL**		**UNITS**
Collector-Base Voltage	V_{CBO}	50	V
Collector-Emitter Voltage	V_{CEO}	50	V
Emitter-Base Voltage	V_{EBO}	3.0	V
Continuous Collector Current	I_C	50	mA
Power Dissipation	P_D	350	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	°C
Thermal Resistance	Θ_{JA}	357	°C/W

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)


		CMPT5086 / CMPT5086B		**CMPT5087**		
SYMBOL	**TEST CONDITIONS**	**MIN**	**MAX**	**MIN**	**MAX**	**UNITS**
I_{CBO}	V_{CB}=10V	-	10	-	10	nA
I_{CBO}	V_{CB}=35V	-	50	-	50	nA
BV_{CBO}	I_C=100µA	50	-	50	-	V
BV_{CEO}	I_C=1.0mA	50	-	50	-	V
BV_{EBO}	I_E=100µA	3.0	-	3.0	-	V
$V_{CE(SAT)}$	I_C=10mA, I_B=1.0mA	-	0.30	-	0.30	V
$V_{BE(SAT)}$	I_C=10mA, I_B=1.0mA	-	0.85	-	0.85	V
f_T	V_{CE}=5.0V, I_C=500µA, f=20MHz	40	-	40	-	MHz
C_{ob}	V_{CB}=5.0V, I_E=0, f=1.0MHz	-	4.0	-	4.0	pF
h_{fe}	V_{CE}=5.0V, I_C=1.0mA, f=1.0kHz	150	600	250	900	
NF	V_{CE}=5.0V, I_C=20mA, R_S=10kΩ, f=10Hz to 15.7kHz	-	3.0	-	2.0	dB
NF	V_{CE}=5.0V, I_C=100µA, R_S=3.0kΩ, f=1.0kHz	-	3.0	-	2.0	dB

		CMPT5086		**CMPT5086B**		**CMPT5087**	
		MIN	**MAX**	**MIN**	**MAX**	**MIN**	**MAX**
h_{FE}	V_{CE}=5.0V, I_C=0.1mA	150	500	200	400	250	800
h_{FE}	V_{CE}=5.0V, I_C=1.0mA	150		200		250	
h_{FE}	V_{CE}=5.0V, I_C=10mA	150		200		250	

CMPT5086
CMPT5086B
CMPT5087

SURFACE MOUNT SILICON
PNP TRANSISTORS

SOT-23 CASE - MECHANICAL OUTLINE



LEAD CODE:
1) Base
2) Emitter
3) Collector

MARKING CODES:
CMPT5086: C2P
CMPT5086B: C2B
CMPT5087: C2Q

DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A	0.003	0.007	0.08	0.18
B	0.006	-	0.15	-
C	-	0.005	-	0.13
D	0.035	0.043	0.89	1.09
E	0.110	0.120	2.80	3.05
F	0.075		1.90	
G	0.037		0.95	
H	0.047	0.055	1.19	1.40
I	0.083	0.098	2.10	2.49
J	0.014	0.020	0.35	0.50

SOT-23 (REV: R3)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centralsemi.com

Worldwide Field Representatives:
www.centralsemi.com/wwreps

Worldwide Distributors:
www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms