

## Honeywell Sensing and Control



[Home](#) > [Products](#) > [Conductive Plastic Potentiometers](#) > [585](#) > [Product Page](#)

### 585SX4Q25F102SP



*Actual product appearance may vary.*

**585 Series Commercial Potentiometer,  
Carbon Element, PC Terminals, 0.05 W  
Power Rating, 1 kOhm Resistance Value**

#### Features

Compact - 9,0 mm [0.354 in] size  
Low cost  
Carbon element  
Linear taper  
Horizontal mount  
Metal shaft and bushings  
PC terminals

#### Potential Applications

Manual controls (throttle, joystick)  
Welding and heating  
Telecommunications

#### Description

The 575 Series is a low cost potentiometer with the benefits of a conductive plastic element. It is panel mounted and the housing and shaft are made from thermoplastic material.

#### Supporting Documentation

[▶ Dimensions](#)

Product Specifications	
Potentiometer Type	Commercial
Element Type	Carbon
Terminal	PC
Power Rating	0.05 W
Resistance Value	1 kOhm
Resistance Tolerance	± 20 %
Linearity	± 5 %
Bushing Thread	M7 [0.276 in] x .75
Bushing Length	7 mm [0.276 in]
Bushing Type	Standard
Shaft Diameter	6 mm [.236 in]
Shaft Length	19,05 mm [0.75 in]
Shaft Ending	Flatted
Body	9.5 mm [0.374 in] square, ± 0.79 mm [0.031 in]

#### My Links

- [→ Login to iCOM](#)
- [→ Login as Rep/AD](#)
- [→ Login as Guest](#)
- [→ Login to Digital University](#)

#### Keyword Search

Search for product and support information.

 [→](#)

#### Product Search

Part number search:

 [→](#)  
 Use (\*) to expand search

[→ Specification Search](#)

Electrical Taper	Linear
Working Voltage (Max.)	50 V
Rotational Life	10000 cycles
Mechanical Rotation	300°
Availability	Global
Series Name	585
UNSPSC Code	4111363300
UNSPSC Commodity	4111363300 Potentiometers

[Terms & Conditions](#) | [Privacy Statement](#) | [Site Map](#)