

Han E F Crimp Contact Au 0.5 mm²/ 20 AWG



Image is for illustration purposes only. Please refer to product description.

| | |
|--------------------|---|
| Part number | 09 33 000 6222 |
| Specification | Han E F Crimp Contact Au 0.5 mm ² / 20 AWG |
| HARTING eCatalogue | https://b2b.harting.com/09330006222 |

Identification

| | |
|-----------------|--------------------|
| Category | Contacts |
| Series | Han E [®] |
| Type of contact | Crimp contact |

Version

| | |
|------------------------|-----------------|
| Gender | Female |
| Contact identification | No groove |
| Manufacturing process | Turned contacts |

Technical characteristics

| | |
|-------------------------|---------------------|
| Conductor cross-section | 0.5 mm ² |
| Conductor cross-section | AWG 20 |
| Operating current | ≤16 A |
| Contact resistance | ≤1 mΩ |
| Stripping length | 7.5 mm |

Material properties

| | |
|---------------------|--|
| Material (contacts) | Copper alloy |
| Surface (contacts) | Gold plated |
| RoHS | compliant with exemption |
| RoHS exemptions | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status | compliant with exemption |
| China RoHS | 50 |



Pushing Performance
Since 1945

Material properties

| | |
|--------------------------------------|--------------------------------------|
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Yes |
| REACH SVHC substances | Lead |
| ECHA SCIP number | b51e5b97-eeb5-438b-8538-f1771d43c17d |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |

Specifications and approvals

| | |
|----------------|-------------------------|
| Specifications | EN 60664-1 IEC 61984 |
|----------------|-------------------------|

Commercial data

| | |
|--------------------------------|--|
| Packaging size | 100 |
| Net weight | 1.5 g |
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140050051 |
| eCl@ss | 27440204 Contact for industrial connectors |