






Verpackt im Gurt in Anlehnung an DIN IEC 60286-3
tape on reel packaging according to DIN IEC 60286-3
Verpackungseinheit: 1000 Stück
packaging unit: 1000 pcs



Anforderungsstufe 1
performance level 1

Kontaktbereich vergoldet
mating area gold plating


Anschlussbereich verzinkt 4-6 μm
terminal area 4-6 μm tin plating

Koplanarität der Anschlüsse $\leq 0,1 \text{ mm}$
coplanarity area of termination $\leq 0,1 \text{ mm}$

1) gültig bei Verwendung von Gegenstecker Federleiste 90° in SMD Ausführung
valid for use by mating female connector 90° in SMT version

*Für die Anforderung nach PG 9 der LV214
(Koshiri-Sicherheit)

*For the requirement of the LV214 PG 9
(Koshiri-security)

Dimension no.		Tolerances Dim. for Information ISO 8015		 All Dimensions in mm	Scale Material 5:1		
<u>Customer drawing:</u> All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.			MiniBridge Male Angeled SMT 10p KS*		
d	10.03.2021	 ERNI International AG Zürichstrasse 72 8306 Brüttisellen - Zürich Switzerland					
Index	Date				474812		I A2
					Class	SRCA	