










1	2	3	4	5
---	---	---	---	---



Circuits	Dim.A	Dim.B	Dim.C	Dim.D	Dim.E	Dim.F	Dim.G
37	63.5	18.2	70.5	48.0	33.0	14.0	15.8

TECHNICAL CHARACTERISTICS

MATERIAL
INSULATOR: ABS RESIN METALIZED
COLOR: CHROMATE CLAIR



ENVIRONMENTAL
FLAMMABILITY RATING: UL94-HB
COMPLIANCE: LEAD FREE AND ROHS

PACKAGING: BAG





NOT COMPATIBLE WITH THE CRIMPING HOUSING:
618 0xx 217 122 & 618 0xx 217 222

RoHS Compliant												D
G				PROJECTION: 	GENERAL TOLERANCE							
F					.X = $\pm$ 0.2							
E					.XX = $\pm$ 0.15							
D	10-NOV-14	VIEWS+PACKG.	AS									
C	20-MAR-13	FLAMABILITY	AR	APPROVAL: NPr	UNIT: MM		DESCRIPTION: WR-DSUB METALIZED PLASTIC HOOD TOP ENTRY 4-40 SCREW				SIZE A4	
B	26-NOV-08	COMPATIBILITY	JP		SCALE:							
A	29-DEC-06	PDF	JP		SHEET: 2/4		WERI PART NO: 6180 xx 253 11					
REV	DATE	FILE	BY		DRAW: AS							



Note:
1.Dimension:
Carton Size:40*28*28(cm)



Carton

Pin.	Pcs/Bag	Pcs/Carton
9	100	600
15	100	400
25	50	300
37	50	300

RoHS Compliant				PROJECTION: 	GENERAL TOLERANCE .X = $\pm$ 0.2 .XX = $\pm$ 0.15	 WÜRTH ELEKTRONIK		
G								
F								
E								
D								
C				APPROVAL: NPr	UNIT: MM	DESCRIPTION: WR-DSUB METALIZED PLASTIC HOOD TOP ENTRY		SIZE
B					SCALE:	4-40 SCREW		
A	10-NOV-14	PDF	AS		SHEET: 3/4	WERI PART NO: 618 0xx 253 11		
REV	DATE	FILE	BY		DRAW: AS			
							A4	

