CMPTA96

SURFACE MOUNT
EXTREMELY HIGH VOLTAGE
PNP SILICON TRANSISTOR



SOT-23 CASE

Central Semiconductor Corp.

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMPTA96 type is a surface mount epoxy molded PNP silicon planar epitaxial transistor designed for extremely high voltage applications.

MARKING CODE: C96

MAXIMUM RATINGS: (T_A=25°C)	**SYMBOL**		**UNITS**
Collector-Base Voltage	V_{CBO}	450	V
Collector-Emitter Voltage	V_{CEO}	450	V
Emitter-Base Voltage	V_{EBO}	6.0	V
Continuous Collector Current	I_C	500	mA
Power Dissipation	P_D	350	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	°C
Thermal Resistance	Θ_{JA}	357	°C/W


ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

SYMBOL	**TEST CONDITIONS**	**MIN**	**TYP**	**MAX**	**UNITS**
I_{CBO}	V_{CB}=400V			100	nA
I_{EBO}	V_{BE}=4.0V			100	nA
BV_{CBO}	I_C=100μA	450	500		V
BV_{CEO}	I_C=1.0mA	450	490		V
BV_{EBO}	I_E=10μA	6.0	9.7		V
$V_{CE(SAT)}$	I_C=1.0mA, I_B=0.1mA			0.20	V
$V_{CE(SAT)}$	I_C=10mA, I_B=1.0mA			0.30	V
$V_{CE(SAT)}$	I_C=50mA, I_B=5.0mA		0.15	0.50	V
$V_{BE(SAT)}$	I_C=10mA, I_B=1.0mA			1.0	V
h_{FE}	V_{CE}=10V, I_C=1.0mA	40			
h_{FE}	V_{CE}=10V, I_C=10mA	50	120	200	
h_{FE}	V_{CE}=10V, I_C=50mA	45			
h_{FE}	V_{CE}=10V, I_C=100mA	25	35		
f_T	V_{CE}=10V, I_C=10mA, f=10MHz	20			MHz
C_{ob}	V_{CB}=20V, I_E=0, f=1.0MHz			7.0	pF
C_{ib}	V_{EB}=0.5V, I_C=0, f=1.0MHz			130	pF

CMPTA96

SURFACE MOUNT
EXTREMELY HIGH VOLTAGE
PNP SILICON TRANSISTOR

SOT-23 CASE - MECHANICAL OUTLINE



LEAD CODE:
1) Base
2) Emitter
3) Collector

MARKING CODE: C96

DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A	0.003	0.007	0.08	0.18
B	0.006	-	0.15	-
C	-	0.005	-	0.13
D	0.035	0.043	0.89	1.09
E	0.110	0.120	2.80	3.05
F	0.075		1.90	
G	0.037		0.95	
H	0.047	0.055	1.19	1.40
I	0.083	0.098	2.10	2.49
J	0.014	0.020	0.35	0.50

SOT-23 (REV: R3)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centralsemi.com

Worldwide Field Representatives:
www.centralsemi.com/wwreps

Worldwide Distributors:
www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms