

Lithium Coin Cell - CR 2354

- Reliable energy for your application
- Standard cells and customized packs
- ESD protection
- UL recognized
- Battery Certification Experts

RoHS compliant · Pb free · REACH compliant · Conflict mineral free

Technical Data Sheet · CR 2354

SPECIFICATIONS

Nominal Voltage	3V
Jauch part number	246539
Nominal Capacity	530 mAh
Standard Load	7.5 kΩ
Standard Curent	0.2 mA
Max. Continuous Current	1 mA
Max. Pulse Current	15 mA
Operating Temperature	-30°C to +70°C*
Weight	Approx. 5.9 gr.
Chemistry	Li/MnO_2
UL1642	MH62838

* In applications where the battery is exposed to temperatures >60°C, please contact Jauch.

DIMENSIONS



DISCHARGE CHARACTERISTICS



TEMPERATURE CHARACTERISTICS



PULSE DISCHARGE CHARACTERISTICS



LOAD VS: CAPACITY



Wide assortment of mounting options, including through hole, surface mount and wire terminals.
Contact Jauch for more information
batterytechnology@jauch.com

Jauch Quartz GmbH • email: batterytechnology@jauch.com
www.jauch.com

06/2019

This information is generally descriptive only and is not intended to make or imply any representation, guarantee or warranty with respect to any cells and batteries. Cell and battery designs/specifications are subject to modification without notice. Contact JAUCH for the latest information.