




MATERIAL NO.	ENGINEERING NO.	FINISHED LENGTH
1200860131	403006A10M010	1M [3 FT 3 IN]
1200860185	404006A10M050	5M [16 FT 5 IN]
1200860579	405006A10M100	10M [32 FT 9.7 IN]


MALE INSERT FRONT VIEW		
3 POLE	4 POLE	5 POLE
		
1 BROWN 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK	1 BROWN 2 WHITE 3 BLUE 4 BLACK 5 GREY

PART NUMBER LEGEND


403006A10M010

3- 3 POLES
4- 4 POLES
5- 5 POLES


FINISHED LENGTH
M001 = .1 METER
M010 = 1 METER
M100 = 10 METER



SCALE 3:1



- NOTES:
- MATERIAL: AS NOTED
 - FINISH: AS NOTED
 - ELECTRICAL:
VOLTAGE: 60VAC/75VDC
CURRENT: 4A (3&4 POLE), 3A (5 POLE)
 - TEMP RATING: -20°C TO +105°C
 - PROTECTION: IP67 (WHEN MATED)
 - COUPLING THREAD: M8x1
 - UL LISTED FILE: E152210
CSA CERTIFIED FILE: LR6837
 - ALL DIMS ARE FOR REFERENCE UNLESS TOLERANCED OR NOTED OTHERWISE



FOR 4-5 POLE ONLY
(SCREW MACHINE CONTACT)

7	WRAP LABEL	VINYL	BLACK/YELLOW
6	OVERMOLD	TPC	YELLOW
5	MALE COUPLING NUT	BRASS	NICKEL PLATED
4	MALE SLEEVE	BRASS	NICKEL PLATED
3	PIN CONTACT	Cu ALLOY	GOLD OVER NICKEL
2	MALE INSERT	PUR	BLACK
1	CABLE, 3-5P, 24AWG	PVC JACKET	YELLOW
ITEM	DESCRIPTION	MATERIAL	FINISH
DOCUMENT STATUS	P1	RELEASE DATE	2022/04/08 14:05:49

POLES	CABLE DIA.
3	0.17 [4.31]
4	0.18 [4.57]
5	0.20 [5.08]

CABLE LENGTH TOLERANCES
<.3M [1FT]: +19mm-0 [+.75in-0]
.3 - .9M [1 - 3FT]: +44.5mm-0 [+1.75in-0]
.9 - 1.8M [3 - 6FT]: +55.6mm-0 [+2.19in-0]
1.8 - 3.7M [6 - 12FT: +88.9mm-0 [+3.50in-0]
3.7 - 7.3M [12 - 24FT]: +165.1mm-0 [+6.50in-0]
7.3-14.6M [24 - 48FT]: +317.5mm-0 [+12.50in-0]
14.6 - 30.5M [48-100FT]: +622.3mm-0 [+24.50in-0]
OVER 30M [100FT] +2% OF FINISHED LENGTH

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION														
	DIMENSION UNITS		SCALE		CURRENT REV DESC: ITEM # 6 WAS PVC, UPDATED MATERIAL TABLE. ADDED STD. NOTES, PART NUMBER LEGEND, TOL. TABLE & CABLE DIA.			molex NANO-CHANGE CORDSET, M8 3-5 POLE, MALE, STRAIGHT, 24 AWG							
	INCH/MM		6:1												
	GENERAL TOLERANCES (UNLESS SPECIFIED)														
	MM		INCH												
	EA = 0	4 PLACES		±	±	EC NO: 701162 DRWN: AKABADI 2021/10/06 CHK'D: RSTONE 2022/03/30 APPR: BWOODMAN 2022/04/08			PRODUCT CUSTOMER DRAWING						
	EC = 0	3 PLACES		±	±										
	EP = 0	2 PLACES		±	±										
	1 PLACE		±	±											
	DIVISIONAL SYMBOLS	0 PLACES		±	±	INITIAL REVISION: DRWN: NKUMAR01 14/07/09 APPR: JFMURPHY 14/07/09			DOCUMENT NUMBER		DOC TYPE	DOC PART	REVISION		
ANGULAR TOL		±	°	SD-120086-132					PSD	001	B				
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS				THIRD ANGLE PROJECTION					DRAWING	SERIES	MATERIAL NUMBER		CUSTOMER	SHEET NUMBER	
Third Angle Projection Symbol		D-SIZE		120086					SEE TABLE		GENERAL MARKET		1 OF 1		