

10	9	8	7	6	5	4	3	2	1										
F										F									
E										E									
	PART NUMBER	ENGINEERING P/N	CABLE LENGTH	DESCRIPTION	POWER PAIR	DATA PAIR	JACKET MATERIAL	JACKET O.D.	VOLTAGE RATING	CURRENT RATING									
	1300390339	DNB00A-M500	50 METERS	MID CABLE	16 AWG	20 AWG	GRAY PVC	.33/8.4mm	300 Volts	4 Amps									
	1300390340	DNB00A-T100	100 METERS	MID CABLE	16 AWG	20 AWG	GRAY PVC	.33/8.4mm	300 Volts	4 Amps									
	1300390343	DNDF00A-M500	50 METERS	THIN FLEX	22 AWG	24 AWG	GRAY TPE	.30/7.6mm	300 Volts	4 Amps									
D	1300390344	DNDF00A-T100	100 METERS	THIN FLEX	22 AWG	24 AWG	GRAY TPE	.30/7.6mm	300 Volts	4 Amps									
	1300390347	DNE00A-M500	50 METERS	TRAY RATED TRUNK	16 AWG	18 AWG	GRAY PVC	.53/13.3mm	600 Volts	8 Amps									
	1300390348	DNE00A-T100	100 METERS	TRAY RATED TRUNK	16 AWG	18 AWG	GRAY PVC	.53/13.3mm	600 Volts	8 Amps									
	1300390349	DNF00A-M500	50 METERS	THICK FLEX	15 AWG	18 AWG	GRAY TPE	.48/12.1mm	300 Volts	4 Amps									
	1300390350	DNF00A-T100	100 METERS	THICK FLEX	15 AWG	18 AWG	GRAY TPE	.48/12.1mm	300 Volts	4 Amps									
C	1300390368	DN00A-M500	50 METERS	THICK	15 AWG	18 AWG	GRAY PVC	.48/12.1mm	300 Volts	4 Amps									
	1300390369	DN00A-T100	100 METERS	THICK	15 AWG	18 AWG	GRAY PVC	.48/12.1mm	300 Volts	4 Amps									
	1300390380	DND00A-M500	50 METERS	THIN	22 AWG	22 AWG	GRAY PVC	.29/7.2mm	300 Volts	4 Amps									
	1300390381	DND00A-T100	100 METERS	THIN	22 AWG	22 AWG	GRAY PVC	.29/7.2mm	300 Volts	4 Amps									
B										B									
A										A									
</																			