


Leiterplatten-Layout Vorschlag für SMT PCB-Layout Proposal for SMT




Anforderungsstufe 1
Performance Level 1

Kontaktbereich vergoldet
Mating Area gold plating


Anschlussbereich verzinkt 4-6 µm
Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0.1 mm
Coplanarity Area of Termination ≤ 0.1 mm

Verpackt in Gurtverpackung
Tape on Reel Packaging
Verpackungseinheit: 320 Stück
Packaging unit: 320 pcs



Abspulrichtung - Reel off Direction



454203		weiß white	0.3	4.5	0.9	3.9	Codierung wie Variante schwarz Encoding such variant black
384465		rot red	3.9	0.9	4.5	0.3	
384464		grün green	2.7	2.1	3.3	1.5	
384463		blau blue	1.5	3.3	2.1	2.7	
384462		schwarz black	0.3	4.5	0.9	3.9	
Ident-Nr. part-no.	Codierung coding	Farbe color	A	B	C	D	Bemerkung note

Copyright by ERNI GmbH
Drawing after notice pursuant to ISO 10006 to be observed

Information:		Tolerances			Scale	3:1			
				All Dimensions in mm					
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.			Designation M 2.54 SRC-P, 4-polig				
		 www.ERNI.com			324069				I A2
d		29.04.2013				Class			
Index		Date				SRCP			