




Note: position of the inspection hole is on the crimp collar for 2.5mm² female contacts

base material: copper alloy
coating: GoldTec

Part no. 09 15 000		Wire gauge	Stripping length	Recommended crimping tools						
male contact	female contact			mm ²	AWG	09 99 000 0888	09 99 000 0001	09 99 000 0110	09 99 000 0021	
6307	6407	0,90	0,14-0,37	26-22	8	X	X			
6304	6404							X	X	
6303	6403	1,15	0,5	20		X	X	X	X	
6305	6405	1,30	0,75	18		X	X	X	X	
6302	6402	1,45	1	18		X	X	X	X	
6301	6401	1,75	1,5	16		X	X	X	X	
6306	6406	2,25	2,5	14		6	X	X		



 All rights reserved Department EL PD		All Dimensions in mm Original Size DIN A4	Scale 2:1	Free size tol.	Ref. Sub.
HARTING D-32339 Espelkamp		Created by SPRENB	Inspected by RIEPE	Standardisation 302077	Date 2021-01-13
Title Han D-SMC FC/MC-CRT-GT		State Final Release			Doc-Key / ECM-Nr. 100133088/UGD/004/C 500000187121
Type TB		Number 09 15 000 6YYY			Rev. C
					Page 1/1