

6

5


4

3

2

1

FRONT VIEW - FEMALE INSERT



- 1 - RED
2 - RED/WHITE
3 - RED/BLACK
4 - GREEN

1.23 [31.2] REF.

4.0 [102] REF.

LENGTH
(SEE CHART)

Ø.68 [17.3] REF.

NOTES:

MATERIALS:

CONTACTS: COPPER ALLOY, GOLD/NICKEL PLATING
CONTACT CARRIER: NYLON, BLACK
MOLDED BODY: PVC, YELLOW
COUPLER: 316 STAINLESS STEEL
INTERFACE O-RING: EPDM

ELECTRICAL:

CURRENT RATING: 4AMP MAX
VOLTAGE RATING: 250V

MECHANICAL:

TEMPERATURE: -20° TO 80°C
INGRESS PROTECTION: IP69K

CABLE SPECIFICATIONS:

CABLE JACKET: PVC, YELLOW
CONDUCTORS: #18/4, PVC

PART NUMBER	ENGINEERING NO.	LENGTH
1200790306	W04001A03M0208	6.56' +3.50" -0 [2.0M +89mm -0]

CUSTOMER PRODUCTION APPROVAL

APPROVED BY: _____

DATE: _____

MUST BE SIGNED AND RETURNED BEFORE
PRODUCTION WILL BEGIN.

RESTRICTED SALES DRAWING

UPDATE COLOR CODE EC NO: WEU2010-0539 DRWN: LHARTMAN 5/7/10 CHKD: TWOLDEGE APPR: JFMURPHY 2010/02/10		QUALITY SYMBOLS ▽=0 ▽C=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH ONLY		SCALE 1:1	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
				mm	INCH	DRAWN BY DATE LHARTMAN 2010/01/05		TITLE MICRO CHANGE ULTRA LOCK 4-POLE FEMALE 90DEGREE #18/4 YELLOW PVC CABLE			
			4 PLACES	±---	±---	CHECKED BY DATE TWOLDEGE 2010/01/15					
			3 PLACES	±---	±.005	APPROVED BY DATE JFMURPHY 2010/02/10		molex MOLEX INCORPORATED			
B		REV	2 PLACES	±---	±.010					SHEET NO.	
			1 PLACE	±---	±.020					1 OF 1	
			ANGULAR ±---°								
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			MATERIAL NO. SEE TABLE		DOCUMENT NO. SD-120079-020			
						SIZE A		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

6

5

4

3

2

1