



VOLTAGE RATING:	300V
AMPERAGE RATING:	max. 4A
PROTECTION CLASS:	IP 68
OPERATING TEMPERATURE:	FLEXING -5°C TO +80 °C STATIC -30 °C TO +80 °C

1200800092	WW4A31K05M020	6.56' +3.50" -0 [2.0M +88.9 -0]
1200800091	WW4A31K05M010	3.28' +2.19" -0 [1.0M +55.6 -0]
1200800090	WW4A31K05M006	1.97' +1.75" -0 [0.6M +44.5 -0]
1200800089	WW4A31K05M003	0.98' +0.75" -0 [0.3M +19.1 -0]
MATERIAL NUMBER	ENGINEERING NUMBER	FINISHED LENGTH

ITEM	COMPONENT	MATERIAL	FINISH
7	LABEL	MYLAR	BLACK/YELLOW
6	O-RING	VITON	GREEN
5	ULTRA-LOCK	BRASS	NICKEL PLATED
4	CONTACT	COPPER ALLOY	Au OVER Ni
3	INSERT	PUR	BLACK
2	OVERMOLD	PUR	YELLOW
1	CABLE #22	TPE	YELLOW

ENTER DESCRIPTION EC NO: WEU2010-0333 DRWN: APOHL_WEU 2010/02/10 CHKD: REISSNER 2010/02/11 APPR: FPACHER 2010/02/25	QUALITY SYMBOLS	$\nabla = 0$ $\square = 0$
	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED) DIMENSION STYLE IN/MM SCALE DESIGN UNITS METRIC THIRD ANGLE PROJECTION
	REV	4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± --- ± 0.1 1 PLACE ± 0.3 ± --- ANGULAR ± ---°
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS SEE NOTES THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

DRAWN BY	DATE	TITLE
APOHL_WEU	2010/02/10	MIC INL. SPLITTER XM TPE 90 DEGREE
CHECKED BY	DATE	
REISSNER	2010/02/11	
APPROVED BY	DATE	
FPACHER	2010/02/24	
MATERIAL NO.	DOCUMENT NO.	
		MOLEX INCORPORATED
		SD-120080-029
		1 OF 1