



Base material: brass

Plating: sliding contact selective plating over nickel  
nickel plated crimp area

Number of contacts per reel: 10000

|   |                |                   |            |
|---|----------------|-------------------|------------|
| D | 09 67 000 7258 | PL2               | PdNi       |
|   | 09 67 000 7257 | PL3               | Flash Gold |
|   | 09 67 000 7256 | PL1               | PdNi       |
|   | Part number    | Performance level | Plating    |

|   |  |  |   |                             |                    |  |
|---|--|--|---|-----------------------------|--------------------|--|
|   | All rights reserved<br>Department EC PD - FR | All Dimensions in mm<br>Original Size DIN A4 |   | Scale<br>5:1                | Free size tol.     | Ref.<br>Sub.   |
|   |  | Created by<br>SONN                           | Inspected by<br>BAGDIKIAN                                     | Standardisation<br>HOFFMANN | Date<br>2015-01-15 | State<br>Final Release                                   |
| HARTING Electronics GmbH<br>D-32339 Espelkamp |  |  | Title<br><b>D-Sub, stamped female AWG 24-28 crimp contact</b> |                             |                    | Doc-Key / ECM-Nr.<br>100607850/UGD/000/A<br>500000083329 |
| Type<br><b>TB</b>                             |  | Number<br><b>0967000725X</b>                 |   |                             | Rev.<br><b>A</b>   | Page<br>1/1  |